

PATENT ASSIGNMENT COVER SHEET

Electronic Version v1.1
Stylesheet Version v1.2

Assignment ID: PATI105847

SUBMISSION TYPE:	NEW ASSIGNMENT
NATURE OF CONVEYANCE:	ASSIGNMENT
CONVEYING PARTY DATA	
Name	Execution Date
Paul Trevethan	03/01/2024
RECEIVING PARTY DATA	
Company Name:	PEC LLC
Street Address:	7941 Shaffer Parkway
City:	Littleton
State/Country:	COLORADO
Postal Code:	80127
PROPERTY NUMBERS Total: 1	
Property Type	Number
Patent Number:	11883936
CORRESPONDENCE DATA	
Fax Number:	
<i>Correspondence will be sent to the e-mail address first; if that is unsuccessful, it will be sent using a fax number, if provided; if that is unsuccessful, it will be sent via US Mail.</i>	
Phone:	7202260651
Email:	galen.peterson@frontrangelegalservices.com
Correspondent Name:	Galen Peterson
Address Line 1:	10901 W. 120th
Address Line 2:	Suite 120
Address Line 4:	Broomfield, COLORADO 80021
ATTORNEY DOCKET NUMBER:	EAP
NAME OF SUBMITTER:	Galen Peterson
SIGNATURE:	Galen Peterson
DATE SIGNED:	03/19/2024
Total Attachments: 10	
source=Assignment_Recordation_11883936#page1.tif	
source=Assignment_Recordation_11883936#page2.tif	
source=Assignment_Recordation_11883936#page3.tif	
source=Assignment_Recordation_11883936#page4.tif	
source=Assignment_Recordation_11883936#page5.tif	

source=Assignment_Recordation_11883936#page6.tif
source=Assignment_Recordation_11883936#page7.tif
source=Assignment_Recordation_11883936#page8.tif
source=Assignment_Recordation_11883936#page9.tif
source=Assignment_Recordation_11883936#page10.tif

RECORDATION FORM COVER SHEET
PATENTS ONLY

To the Director of the U.S. Patent and Trademark Office: Please record the attached documents or the new address(es) below.

1. Name of conveying party(ies)

Paul Trevethan

Additional name(s) of conveying party(ies) attached? ☐ Yes ☒ No

3. Nature of conveyance/Execution Date(s):

Execution Date(s) 03/01/2024

- ☒ Assignment ☐ Merger
☐ Security Agreement ☐ Change of Name
☐ Joint Research Agreement
☐ Government Interest Assignment
☐ Executive Order 9424, Confirmatory License
☐ Other _____

2. Name and address of receiving party(ies)

Name: PEC LLC

Internal Address: _____

Street Address: 7941 Shaffer Parkway

City: Littleton

State: Colorado

Country: USA Zip: 80127

Additional name(s) & address(es) attached? ☐ Yes ☒ No

4. Application or patent number(s):

☒ This document serves as an Oath/Declaration (37 CFR 1.63).

A. Patent Application No.(s)

B. Patent No.(s)

11,883,936 B2

Additional numbers attached? ☐ Yes ☒ No

5. Name and address to whom correspondence concerning document should be mailed:

Name: Galen PEterson

Internal Address: _____

Street Address: 10901 W 120th
Suite 120

City: Broomfield

State: Colorado Zip: 80021

Phone Number: 720-226-0651

Docket Number: EAP

Email Address: galen.peterson@frontrangelegalservices.com

6. Total number of applications and patents involved: ¹ _____

7. Total fee (37 CFR 1.21(h) & 3.41) \$ _____

- ☐ Authorized to be charged to deposit account
☐ Enclosed
☒ None required (government interest not affecting title)

8. Payment Information

Deposit Account Number _____

Authorized User Name _____

9. Signature: _____ /Galen Peterson/

3/19/2024

Signature

Date

Galen Peterson Reg# 78402

Name of Person Signing

Total number of pages including cover sheet, attachments, and documents:

10

Documents to be recorded (including cover sheet) should be faxed to (571) 273-0140, or mailed to:
Mail Stop Assignment Recordation Services, Director of the USPTO, P.O.Box 1450, Alexandria, V.A. 22313-1450

PATENT
REEL: 066829 FRAME: 0394

WAIVER, ASSIGNMENT AND TRANSFER AGREEMENT

WHEREAS, Paul Trevethan (the “**Assignor**”) may have invented certain new and useful improvements to the Oscillating Tool Adaptor, US Patent # 11,883,936 issued January 30, 2024 (the “**Apparatus**”);

WHEREAS, PEC LLC., a Colorado Limited Liability Company residing at 7941 Shaffer Parkway, Littleton, CO 80127, US (the “**Assignee**”), desires to acquire the entire right, title and interest in and to the Apparatus and any and all Patent Applications, Letters Patent or similar legal protection, foreign or domestic, to be obtained therefor;

WHEREAS, Assignee entered into an agreement with Assignor on or about January 2021 to contribute to the design and function of the Apparatus, and for other design services;

WHEREAS, Assignee has submitted a patent application for one or more inventions embodied by the Apparatus and the application has been issued January 30th, 2024 (the “**Application**”). See Exhibit A.


NOW, THEREFORE, for good and valuable consideration, the receipt and adequacy of which are hereby acknowledged, Assignor hereby assigns and transfers to Assignee, its successors and assigns, its entire right, title, interest in and to the Apparatus and the Application; all inventions, designs, utility models, and creative works described or shown in or embodied by the apparatus and the device designs associated with the apparatus; all applications claiming the benefit of or priority to the Application (including without limitation divisionals, continuations, continuations-in-part, reexaminations, reissues, supplemental examinations, continued prosecution applications, post-grant reviews, inter partes reviews, renewals, and extensions); all applications to which the Application claims priority or of which the Application claims benefit (including without limitation provisional applications); all substitutes of any of the foregoing; all foreign applications corresponding to or claiming priority to any of the foregoing; all Letters Patent or similar legal protection issuing on any of the foregoing; all rights and benefits of any of the foregoing under the Paris Convention for the protection of Industrial Property, the Patent Cooperation Treaty, the European Patent Convention, the Gulf Cooperation Council, and any applicable treaty or convention, including the right to claim the priority benefit of any of the foregoing; all rights of action and damages for any past, present, or future infringement of any of the foregoing, including all rights of action and damages arising from publication or issuance of any of the foregoing; with all such rights to be held and enjoyed by Assignee as fully and entirely as such rights would have been held and enjoyed by Assignor had this Assignment not been made.

Assignor authorizes the Commissioner of Patents and Trademarks of the United States or foreign equivalent thereof to issue the Letters Patent or similar legal protection for any of the foregoing to Assignee. Assignor authorizes Assignee, its successors and assigns, and its representatives, to insert in or on this Assignment the filing date and application number of the Application or any application to which this instrument pertains, including any further identification which may be necessary or desirable in order to comply with the rules of the U.S. Patent and Trademark Office

or foreign equivalent thereof for recordation of this assignment. Assignor authorizes Assignee, its successors and assigns or anyone it may properly designate, to apply for Letters Patent or similar legal protection, in its own name if desired, in any and all foreign countries.

Assignor represents to Assignee, its successors and assigns, that it has not and will not execute any writing or do any act whatsoever conflicting with this Assignment. Assignor further represents to Assignee, its successors and assigns, that it has valid agreements in place with any and all of its employees and/or agents who may have contributed certain new and useful improvements to the Apparatus, or who may be inventors of the Application, and by such agreements, Assignor holds all right, title, and interest in and to such certain new and useful improvements to the Apparatus with respect to its employees and/or agents and/or such inventors. Assignor will at any time upon request, without additional consideration, but at the expense of Assignee, its successors and assigns, execute such additional writings and do such additional acts as Assignee, its successors or assigns, may deem desirable to perfect Assignee's enjoyment of this grant, and render all assistance in making application for and obtaining, maintaining, and enforcing the Letters Patent or similar legal protection on the inventions, the Application, and corresponding applications in any and all countries, including without limitation executing all papers and providing any evidence necessary for the advancement of any administrative or judicial proceeding relating thereto.


IN WITNESS WHEREOF, Assignor has executed this Assignment on the date indicated below.

Signature:  737EAE3A368940B...

Name: Paul Trevethan

Date: 3/1/2024

Acknowledged and Agreed by PEC LLC.
as of 3/8/2024

By:  DE86641151214E8...
(signature)

Name: Cyrus Perme
Title:

(12) **United States Patent**
Trevethan

(10) **Patent No.:** **US 11,883,936 B2**
(45) **Date of Patent:** **Jan. 30, 2024**

(54) **OSCILLATING TOOL ADAPTER**

(71) Applicant: **Paul Trevethan**, Aurora, CO (US)

(72) Inventor: **Paul Trevethan**, Aurora, CO (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 122 days.

(21) Appl. No.: **17/446,086**

(22) Filed: **Aug. 26, 2021**

(65) **Prior Publication Data**

US 2023/0060612 A1 Mar. 2, 2023

(51) **Int. Cl.**
B25B 28/00 (2006.01)

(52) **U.S. Cl.**
CPC **B25B 28/00** (2013.01)

(58) **Field of Classification Search**
CPC B25B 28/00; B25B 27/00
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

87,531 A *	3/1869	Wilcox	B25B 17/00	81/57.3
5,441,450 A	8/1995	Fein et al.			
6,550,357 B1 *	4/2003	Freeman	B25B 13/00	81/177.2
7,052,383 B2	5/2006	Sieber			
8,065,936 B2 *	11/2011	Tutino	B25B 17/02	81/57
8,182,316 B2	5/2012	Peisert			
8,387,717 B2	3/2013	Kildevaeld			

8,403,341 B2	3/2013	Zaiser et al.			
9,073,195 B2	7/2015	Kaye, Jr. et al.			
9,242,361 B2	1/2016	Kaye, Jr. et al.			
9,248,562 B2	2/2016	Bernardi et al.			
9,833,872 B2	12/2017	Rubens			
9,845,840 B2 *	12/2017	Holloway	F16H 1/06	
10,040,186 B2	8/2018	Kaye, Jr. et al.			
10,245,716 B2	4/2019	Kaye, Jr. et al.			
10,265,778 B2	4/2019	Kaye, Jr. et al.			
10,702,927 B2	7/2020	Kaye, Jr. et al.			
11,090,783 B2 *	8/2021	Angello	F16H 57/02	
2004/0132392 A1	7/2004	Bohler			
2008/0196554 A1 *	8/2008	Tutino	B25B 23/0035	81/57.3
2008/0240884 A1 *	10/2008	Dahners	B25B 13/485	411/190
2013/0193655 A1	8/2013	Kaye, Jr. et al.			
2017/0210000 A1 *	7/2017	Lee	B25G 1/063	
2019/0176315 A1	6/2019	Kaye, Jr. et al.			
2023/0060612 A1 *	3/2023	Trevethan	B25B 28/00	

* cited by examiner


Primary Examiner — Lee D Wilson

(74) *Attorney, Agent, or Firm* — John A. Arsenault; Galen Peterson

(57) **ABSTRACT**

An adapter assembly is provided for converting a first oscillating motion from an oscillating tool to a second oscillating motion at a wheel that is useful for applying polymers and other films to doors, windows, and other surfaces or for applying rubber gaskets around a window during installation of the window. The adapter assembly is provided with an adapter that tapers in the anterior direction when attached to an oscillating tool. An axle is provided at the distal end of the adapter and attaches to a concentrically aligned bearing within the wheel.

11 Claims, 3 Drawing Sheets






FIG. 1




FIG. 2A




FIG. 2B




FIG. 2C




FIG. 3A




FIG. 3B




FIG. 4A




FIG. 4B

1

OSCILLATING TOOL ADAPTER**STATEMENT REGARDING FEDERALLY
SPONSORED RESEARCH AND
DEVELOPMENT**

Not Applicable.

FIELD OF INVENTION

Embodiments of the present invention relate to the field of oscillating tool adapters and relate more specifically to an apparatus and method for installing windows and applying polymeric materials to surfaces.

BACKGROUND OF DISCLOSURE

Adhesive vinyl and other polymers are frequently applied to windows and other surfaces for advertising or for displaying various types of information. Numerous techniques for applying adhesive polymers to glass have been known. Rollers and scraping tools are inexpensive devices used by many in the glazing industry; however, effectively removing trapped air pockets between the polymer sheet and the target surface with these devices is quite difficult, especially with larger or thicker polymers sheets.

Various power tools for applying sheets onto surfaces have also been attempted. These power tools often cause discomfort to the user after prolonged use in addition to irreversible damage to the sheet or to the target surface. Furthermore, the process of installing the windows themselves generally requires the application of a polymeric material, or rubber gasket, about the edges of the window being installed. Difficulties arise from attempting to guide a typical installation tool along the edges of the window that contact the frame surrounding the window, and often the result is a non-uniform installation of the rubber gasket or damage to the window.

Thus, there is a need for a device that can effectively apply sheets onto target surfaces, remove air pockets trapped between the sheet and surface, and reduce carpal tunnel and other discomfort or injuries to the hands of the user. There is also a need for a device that can adequately apply rubber gasket to the surrounding edges during window installation.

SUMMARY OF THE DISCLOSURE

The present invention provides an oscillating tool adapter system and method for applying an adhesive sheet to a target surface or for applying a rubber gasket to the area surrounding a window being installed. In a preferred embodiment, the tool adapter system comprises an adapter assembly securable onto an oscillating tool and directed towards the anterior direction of the tool, the adapter assembly comprising an adapter secured to the oscillating tool at one end portion, an axle attached thereto the other end portion of the adapter, and a wheel comprising a bearing concentrically aligned within the wheel. During use of the tool adapter system, a first oscillatory, or vibrational motion from the oscillating tool is transmitted to the wheel whereby a second oscillatory motion is present. The second oscillatory motion acts to agitate or vibrate an adhesive sheet into proper position when the tool adapter system is pressed against the sheet onto the target surface and/or moved laterally about the sheet by a user. The second oscillatory motion may also be used to install a rubber gasket surrounding a window during

2

It is a feature of the present invention that a first oscillatory motion generated by an oscillating tool is transmitted or converted to a second oscillatory motion at a wheel, the second oscillatory motion at the wheel being useful for applying polymers onto surfaces or for installing a rubber gasket to the surrounding edges of a window.

It is a feature of the present invention that the size, weight distribution, shape or form of the wheel may be varied to increase effectiveness of the tool adapter system for particular applications.

Embodiments include one, more, or any combination of all of the features listed above. Other features and advantages of the present invention will become apparent from the following more detailed description, taken in conjunction with the accompanying, which illustrate, by way of example, the principles of the invention.

DESCRIPTION OF THE DRAWINGS

FIG. 1 is a side perspective view of tool adapter system in use to apply an adhesive sheet **80** to a target surface **90**, in accordance with an exemplary embodiment of the present invention;

FIG. 2A is a top perspective view of an adapter, in accordance with an exemplary embodiment of the present invention;

FIG. 2B is a bottom perspective view of the adapter shown in FIG. 2A, in accordance with an exemplary embodiment of the present invention;

FIG. 2C is a side sectional view of the adapter shown in FIG. 2A taken along line **6**, in accordance with an exemplary embodiment of the present invention;

FIG. 3A is a bottom view of a wheel, bearing, and axle, in accordance with an exemplary embodiment of the present invention;

FIG. 3B is a sectional view of the wheel, bearing, and axle shown in FIG. 3A taken along line **7**, in accordance with an exemplary embodiment of the present invention;

FIG. 4A is a bottom view of an alternate embodiment of a wheel, bearing, and axle, in accordance with an exemplary embodiment of the present invention; and

FIG. 4B is a sectional view of the wheel, bearing, and axle shown in FIG. 4A taken along line **8**, in accordance with an exemplary embodiment of the present invention.

**DETAILED DESCRIPTION OF THE
DISCLOSED EMBODIMENT**

Illustrative embodiments of the invention are described below in the accompanying Figures. The following detailed description provides detailed schematics for a thorough understanding of and an enabling description for these embodiments. One having ordinary skill in the art will understand that the invention may be practiced without certain details. In other instances, well-known structures and functions have not been shown or described in detail to avoid unnecessarily obscuring the description of the embodiments. In the description, terms such as "upper" and "lower" should be construed to refer to orientation as then described or as shown in the drawings under discussion. The terms are for convenience of description and do not require that the system or component of the system be operated in a particular orientation.

FIG. 1 is a side perspective view of a tool adapter system **100** in use to apply an adhesive sheet **80** to a target surface **90**, in accordance with an exemplary embodiment of the

3

system **100** comprises an oscillating tool **10** and an adapter assembly **12** comprising an adapter **20**, an axle **40**, a wheel **50**, a bearing **51**, and a nut **33**. The oscillating tool **10** may be a multi-tool or any device designed to cause vibrational or oscillatory motion with a frequency range of 2,000 to 40,000 cycles per minute. The nut **33** may be a Nyloc nut or other type of nut designed to resist loosening due to vibrations. During operation of the tool adapter system **100**, a first oscillating motion provided by the oscillating tool **10** is transmitted to the wheel **50**, wherein a second oscillating motion having oscillating characteristics that are useful for applying rubber gaskets around windows during installation or for applying polymers onto surfaces is achieved. The second oscillating motion of the wheel **50** generally varies as a user applies a downward force at the wheel **50** against a surface. The adhesive sheet **80** may be a polymer such as vinyl and may further comprise an adhering surface designed to further adherence of the adhesive sheet **80** to a target surface **90**. Target surface **90** may be a glassy material in use as a window, wall, dome, or other enclosure surface.

FIG. 2A is a top perspective view of an adapter **20**, in accordance with an exemplary embodiment of the present invention. FIG. 2B is a bottom perspective view of the adapter **20** shown in FIG. 2A, in accordance with an exemplary embodiment of the present invention. FIG. 2C is a side sectional view of the adapter **20** shown in FIG. 2A taken along line **6**, in accordance with an exemplary embodiment of the present invention. The adapter **20** tapers from a proximal end portion **21** towards a distal end portion **22** in the anterior direction **3** with respect to an oscillating tool **10**. The tapering of adapter **20** provides for adequate transmission of the first oscillatory motion to the wheel and for a lighter weighted assembly.

Defined within the volume of the upper portion **23** of the adapter **20** may be a key slot **25** centered about a first concentric axis **1**. The key slot **25** is designed to match and securely attach to the locking mechanism **11** of the oscillating tool **10** so that the adapter **20** is resistant to loosening. Defined within the volume of the distal end portion **22** of the adapter **20** may be a threaded axle housing **26** centered about a second concentric axis **2** and designed to receive and secure the axle **40** therethrough. The upper end portion **41** of the axle **40** is generally designed to rotatably insert there-through the threading of axle housing **26** about concentric axis **2** and is secured in place by the nut **33**. The lower end portion **42** of the axle **40** may protrude radially outward to secure or bolt the wheel **50** to the adapter **20**. The axle **40** may be manufactured from a substantially rigid polymer, metal, or other strong and durable material.

FIG. 3A is a bottom view of a wheel **50**, bearing **51**, and axle **40**, in accordance with an exemplary embodiment of the present invention. FIG. 3B is a sectional view of the wheel **50**, bearing **51**, and axle **40** shown in FIG. 3A taken along line **7**, in accordance with an exemplary embodiment of the present invention. The wheel **50** comprises a bearing **51** concentrically aligned within the wheel **50**, wherein the bearing **51** provides the wheel **50** rotational freedom about the second concentric axis **2**. The dimensions of the wheel **50** may be varied depending on the application.

FIG. 4A is a bottom view of an alternate embodiment of a wheel **50**, bearing **51**, and axle **40**, in accordance with an exemplary embodiment of the present invention. FIG. 4B is a sectional view of the wheel **50**, bearing **51**, and axle **40** shown in FIG. 4A taken along line **8**, in accordance with an exemplary embodiment of the present invention. In this embodiment, a disk **42** is provided for guiding the wheel **40**

4

surrounding frame, the disk protruding radially beyond the wheel **42** and secured directly to the upper portion of the wheel **42**. The inventor contemplates that the size, weight, and dimensions of the wheel **50** and bearing **51** may be varied depending on the size and weight of adhesive sheet **80** as well as tendency of the sheet **80** to adhere to target surface **90**.

Furthermore, the dimensions of the adapter **20** and axle **40** may be varied depending on the application. In an example embodiment, a 4 ampere rated oscillating tool is anteriorly equipped with an adapter assembly **12** having an adapter **20** that is 10.2 cm (4 inches) long, 1.9 cm ($\frac{3}{4}$ inch) thick, and tapers from 2.54 cm (1 inch) to 0.635 cm ($\frac{1}{4}$ inch), an axle **40** that is 5.1 cm (2 inches) long with a 0.635 cm ($\frac{1}{4}$ inch) diameter, a 0.635 cm ($\frac{1}{4}$ inch) diameter nyloc nut **33**, and a wheel **50** that is 5.1 cm (2 inches) in diameter and 2.54 cm (1 inch) thick. This example device is suitable for applying vinyl films to flat glass surfaces without damaging the film or the glass surface. This example embodiment may further provide a disk **42** that is up to 7.6 cm (3 inches) in diameter.

In an alternate example embodiment of the present invention, a 3 ampere rated oscillating tool is anteriorly equipped with an adapter assembly **12** having an adapter **20** that is 10.2 cm (4 inches) long, 1.9 cm ($\frac{3}{4}$ inch) thick, and tapers from 7.6 cm (3 inch) to 2.54 cm (1 inch), an axle **40** that is 7.6 cm (3 inches) long with a 1.27 cm ($\frac{1}{2}$ inch) diameter, a 1.27 cm ($\frac{1}{2}$ inch) diameter nyloc nut **33**, and a wheel **50** that is 3.8 cm (1½ inches) in diameter and 2.54 cm (1 inch) thick. This example device is also suitable for applying vinyl films to a window without damaging the film or the window.

In various embodiments, the wheel **50** may be manufactured of a soft polymeric material such as, but not limited to, polyurethanes. In some embodiments, the wheel **50** may taper towards the axle **40** proximate to the lower end portion **42** of the axle **40**. In embodiments having a disk section **52**, the disk section **52** may be manufactured of a soft polymeric material or a rigid and durable polymeric material.

While particular embodiments of the invention have been described and disclosed in the present application, it is clear that any number of permutations, modifications, or embodiments may be made without departing from the spirit and the scope of this invention. Accordingly, it is not the inventor's intention to limit this invention in this application, except as by the claims.

Particular terminology used when describing certain features or aspects of the invention should not be taken to imply that the terminology is being redefined herein to be restricted to any specific characteristics, features, or aspects of the invention with which that terminology is associated. In general, the terms used in the claims should not be construed to limit the invention to the specific embodiments disclosed in the specification, unless the above Detailed Description section explicitly defines such terms. Accordingly, the actual scope of the invention encompasses not only the disclosed embodiments, but also all equivalent ways of practicing or implementing the invention.

The above detailed description of the embodiments of the invention is not intended to be exhaustive or to limit the invention to the precise embodiment or form disclosed herein or to the particular field of usage mentioned in this disclosure. While specific embodiments of, and examples for, the invention are described above for illustrative purposes, various equivalent modifications are possible within the scope of the invention, as those skilled in the relevant art will recognize. Also, the teachings of the invention provided herein can be applied to other systems, not necessarily the

5

various embodiments described above can be combined to provide further embodiments.

All of the above patents and applications and other references, including any that may be listed in accompanying filing papers, are incorporated herein by reference. Aspects of the invention can be modified, if necessary, to employ the systems, functions, and concepts of the various references described above to provide yet further embodiments of the invention.

In general, the terms used in the claims should not be construed to limit the invention to the specific embodiments disclosed in the specification, unless the above Detailed Description section explicitly defines such terms. Accordingly, the actual scope of the invention encompasses not only the disclosed embodiments, but also all equivalent ways of practicing or implementing the invention under the claims.

In light of the above "Detailed Description," Inventor may make changes to the invention. While the detailed description outlines possible embodiments of the invention and discloses the best mode contemplated, no matter how detailed the above appears in text, the invention may be practiced in a myriad of ways. Thus, implementation details may vary considerably while still being encompassed by the spirit of the invention as disclosed by the inventor. As discussed herein, specific terminology used when describing certain features or aspects of the invention should not be taken to imply that the terminology is being redefined herein to be restricted to any specific characteristics, features, or aspects of the invention with which that terminology is associated.

What is claimed is:

1. An adapter assembly for an oscillating tool, said adapter assembly comprising:
 an adapter having an upper portion, a lower portion, a proximal end portion, and a distal end portion;
 wherein said adapter has a top edge and a bottom edge, wherein the top edge and bottom edge congruently intersect at the distal end portion, and the top edge and bottom edge diverge therefrom; the proximal end portion comprising a width that spans between the top edge and bottom edge;
 wherein defined within a volume of said distal end portion of said adapter is a threaded axle housing;
 an axle having an upper end portion and a lower end portion;
 a wheel comprising a bearing concentrically aligned within said wheel;
 defined within a volume of said upper portion and said proximal end portion of said adapter is a key slot centered about a first concentric axis.

6

2. The adapter assembly of claim 1, further comprising a nut for securing said axle to said adapter, said nut fastening to said upper end portion of said axle.

3. The adapter assembly of claim 1, wherein said nut is a nyloc nut.

4. The adapter assembly of claim 1, wherein said key slot is designed to match and secure said adapter to said oscillating tool.

5. An adapter assembly for an oscillating tool, said adapter assembly comprising:

an adapter having an upper portion, a lower portion, a proximal end portion, and a distal end portion;

an axle having an upper end portion and a lower end portion;

a wheel comprising a bearing concentrically aligned within said wheel;

wherein defined within a volume of said distal end portion of said adapter is a threaded axle housing centered about a second concentric axis and designed to receive and secure said axle therethrough.

6. The adapter assembly of claim 5, wherein said upper end portion of said axle is rotatably insertable therethrough said axle housing about said second concentric axis.

7. The adapter assembly of claim 6, wherein said upper end portion is secured in place by a nut.

8. The adapter assembly of claim 1, wherein said lower end portion of said axle protrudes radially outward for securing or bolting said wheel to said adapter.

9. The adapter assembly of claim 1, wherein said wheel tapers towards said axle proximate to said lower end portion of said axle.

10. The adapter assembly of claim 1, further comprising a disk directly attached to said wheel and radially protruding beyond said wheel.

11. An adapter assembly for converting a first oscillating motion from an oscillating tool to a second oscillating motion, said second oscillating motion being useful for applying an adhesive sheet or film to a target surface, said adapter assembly comprising:

an equilateral-triangle-shaped adapter having an upper portion, a lower portion, a proximal end portion comprising a oscillating tool key lock configured to removably couple with an oscillating tool, and a distal end portion, wherein defined within a volume of said distal end portion is a threaded axle housing;

a wheel comprising a bearing concentrically aligned within said wheel; and

an axle having an upper end portion and a lower end portion, said upper end portion being concentrically aligned with and insertable therethrough said axle housing of said adapter, said lower end portion securely fastened to said bearing.

* * * * *