

## PATENT ASSIGNMENT COVER SHEET

Electronic Version v1.1  
Stylesheet Version v1.2

Assignment ID: PATI296521

<b>SUBMISSION TYPE:</b>	RESUBMISSION
<b>NATURE OF CONVEYANCE:</b>	ASSIGNMENT
<b>RESUBMIT DOCUMENT ID:</b>	508491685
<b>CONVEYING PARTY DATA</b>	
<b>Name</b>	<b>Execution Date</b>
Mr. Brian Raivo	03/15/2024
<b>RECEIVING PARTY DATA</b>	
<b>Company Name:</b>	Net Zero Platforms Europe Ltd.
<b>Street Address:</b>	Grosvenor House
<b>Internal Address:</b>	11 St. Paul's Square
<b>City:</b>	Birmingham
<b>State/Country:</b>	UNITED KINGDOM
<b>Postal Code:</b>	B3 1RB
<b>PROPERTY NUMBERS Total: 1</b>	
<b>Property Type</b>	<b>Number</b>
Patent Number:	10435295
<b>CORRESPONDENCE DATA</b>	
<b>Fax Number:</b>	
<i>Correspondence will be sent to the e-mail address first; if that is unsuccessful, it will be sent using a fax number, if provided; if that is unsuccessful, it will be sent via US Mail.</i>	
<b>Phone:</b>	07712010501
<b>Email:</b>	davidjonathanjackson@gmail.com
<b>Correspondent Name:</b>	Mr. David Jonathan Jackson
<b>Address Line 1:</b>	Flat 16, Churchill Court, Kelham Gardens
<b>Address Line 2:</b>	Kelham Gardens
<b>Address Line 4:</b>	MARLBOROUGH, UNITED KINGDOM SN8 1LD
<b>NAME OF SUBMITTER:</b>	David Jackson
<b>SIGNATURE:</b>	David Jackson
<b>DATE SIGNED:</b>	06/13/2024
	This document serves as an Oath/Declaration (37 CFR 1.63).
<b>Total Attachments: 29</b>	
source=Net Zero Platforms Europe acquisition of IP Brain Raivo LOI and SPA 1#page1.tif	
source=Net Zero Platforms Europe acquisition of IP Brain Raivo LOI and SPA 1#page2.tif	
source=Net Zero Platforms Europe acquisition of IP Brain Raivo LOI and SPA 1#page3.tif	

source=Net Zero Platforms Europe acquisition of IP Brain Raivo LOI and SPA 1#page4.tif  
source=Net Zero Platforms Europe acquisition of IP Brain Raivo LOI and SPA 1#page5.tif  
source=Net Zero Platforms Europe acquisition of IP Brain Raivo LOI and SPA 1#page6.tif  
source=Net Zero Platforms Europe acquisition of IP Brain Raivo LOI and SPA 1#page7.tif  
source=Net Zero Platforms Europe acquisition of IP Brain Raivo LOI and SPA 1#page8.tif  
source=Net Zero Platforms Europe acquisition of IP Brain Raivo LOI and SPA 1#page9.tif  
source=Net Zero Platforms Europe acquisition of IP Brain Raivo LOI and SPA 1#page10.tif  
source=Net Zero Platforms Europe acquisition of IP Brain Raivo LOI and SPA 1#page11.tif  
source=Net Zero Platforms Europe acquisition of IP Brain Raivo LOI and SPA 1#page12.tif  
source=Net Zero Platforms Europe acquisition of IP Brain Raivo LOI and SPA 1#page13.tif  
source=Net Zero Platforms Europe acquisition of IP Brain Raivo LOI and SPA 1#page14.tif  
source=Net Zero Platforms Europe acquisition of IP Brain Raivo LOI and SPA 1#page15.tif  
source=Net Zero Platforms Europe acquisition of IP Brain Raivo LOI and SPA 1#page16.tif  
source=Net Zero Platforms Europe acquisition of IP Brain Raivo LOI and SPA 1#page17.tif  
source=Net Zero Platforms Europe acquisition of IP Brain Raivo LOI and SPA 1#page18.tif  
source=Net Zero Platforms Europe acquisition of IP Brain Raivo LOI and SPA 1#page19.tif  
source=Net Zero Platforms Europe acquisition of IP Brain Raivo LOI and SPA 1#page20.tif  
source=Net Zero Platforms Europe acquisition of IP Brain Raivo LOI and SPA 1#page21.tif  
source=Net Zero Platforms Europe acquisition of IP Brain Raivo LOI and SPA 1#page22.tif  
source=Net Zero Platforms Europe acquisition of IP Brain Raivo LOI and SPA 1#page23.tif  
source=Net Zero Platforms Europe acquisition of IP Brain Raivo LOI and SPA 1#page24.tif  
source=Net Zero Platforms Europe acquisition of IP Brain Raivo LOI and SPA 1#page25.tif  
source=Net Zero Platforms Europe acquisition of IP Brain Raivo LOI and SPA 1#page26.tif  
source=Net Zero Platforms Europe acquisition of IP Brain Raivo LOI and SPA 1#page27.tif  
source=Net Zero Platforms Europe acquisition of IP Brain Raivo LOI and SPA 1#page28.tif  
source=Net Zero Platforms Europe acquisition of IP Brain Raivo LOI and SPA 1#page29.tif

**SALES PURCHASE AGREEMENT  
BY AND BETWEEN  
NET ZERO PLATFORMS EUROPE LTD. AND MR. BRIAN RAIVO**

This Sales Purchase Agreement ("Agreement") is made and entered into as of 15<sup>th</sup> March 2024 by and between Net Zero Platforms Europe Ltd. ("Buyer"), a business operating as an energy technology business, with its principal place of business located at 11 St. Paul's Square, Birmingham B3 1RB, and Mr. Brian Raivo and/or assigns ("Seller"), 2530 North 26<sup>th</sup> West, Idaho Falls, Idaho 83402.

The Buyer has started an engagement process with a major global oil and gas company to deploy technology platforms and know-how for the purpose of generating income, using the patents, Intellectual Property (IP), materials, software, drawings, and technical data, acquired from the Seller under this Agreement.

**Recitals**

WHEREAS, the Buyer and Seller have executed a Letter of Intent (LOI) dated 11<sup>th</sup> September 2023 (Exhibit A), which outlines the arrangement for the purchase of U.S. Patent #10,435,295 titled "Coupling an Electric Furnace with a Liquid Fuel Synthesis Process to Improve Performance When Processing Heterogeneous Wastes" (Exhibit B), related materials, and technical data related to associated work (collectively, the "Intellectual Property" or "IP", Exhibit C);

WHEREAS the Seller represents and warrants that they are the sole owner of the IP apart from where Thomas L. Eddy is named as co-author, and has the full legal right and authority to enter into this Agreement and to sell, assign, and transfer the IP to the Buyer.

Notwithstanding the above, the Seller hereby guarantees full title of the IP and agrees to transfer the same to the Buyer free from any liens, charges, encumbrances, claims, or third-party rights.

Pursuant to the LOI, the Buyer has made an initial payment as agreed;

WHEREAS the Parties wish to complete the purchase and transfer of the IP in accordance with the terms set forth in the LOI;

NOW, THEREFORE, in consideration of the mutual covenants and agreements contained herein, and for other good and valuable consideration, the receipt and sufficiency of which are hereby acknowledged, the Parties agree as follows in good faith:

BR  


**SALES PURCHASE AGREEMENT  
BY AND BETWEEN  
NET ZERO PLATFORMS EUROPE LTD. AND MR. BRIAN RAIVO**

**1. Sale and Purchase of Intellectual Property**

1.1 The Seller hereby agrees to sell, convey, transfer, and assign to the Buyer, and the Buyer hereby agrees to purchase from the Seller, the Intellectual Property described in Exhibit B attached hereto, upon the terms and subject to the conditions set forth in this Agreement.

The Seller also agrees to support any subsequent ownership transfer process that may be required by the patent office or such regulatory body(s) in recognition of this Agreement and the rights of the new owner and Buyer. The Buyer will cover all such agreed-upon costs.

**2. Purchase Price**

2.1 The total purchase price for the IP shall be US\$12,000.00, inclusive of the initial payment of US\$1,000.00 already made by the Buyer as per the LOI.

2.2 The balance of the purchase price, US\$11,000.00, shall be paid to the Seller at the closing of this transaction.

**3. Closing**

3.1 The closing of the purchase and sale of the IP ("Closing") shall take place on Closing Date, or at such other time and place as the Parties may mutually agree upon.

3.2 At Closing, the Buyer shall pay the balance of the purchase price to the Seller, and the Seller shall deliver to the Buyer all necessary documents to effectuate the transfer and the assignment of the patent to the Buyer, and the Seller shall make the Exhibit C items available for pickup or mutually agreed shipping arrangement by the Buyer and Seller. The Seller makes an irrevocable commitment to Buyer to assign and or support assignment to Buyer, deliver and or support pick up of any remaining IP that is not transferred at close.

3.3 The proposed closing date is March 18<sup>th</sup> or sooner, 2024.

**4. Royalties**

4.1 The Buyer agrees to pay the Seller royalties based on five percent (5%) of the "Net Revenue" from liquid equivalent fuel quantities produced and sold using the IP for fourteen (14) years following the signing of this Agreement.

For the purposes of this Agreement, "Net Revenues" shall mean the gross revenue actually received by the Buyer from the use, sale, license, or other exploitation of the IP in the oil and gas sector, less the sum of the following deductions: costs of goods sold ("COGS"), operating expenses ("OPEX"), all direct costs attributable to the production and distribution of the product, services incurred from the use of the

 BR

**SALES PURCHASE AGREEMENT  
BY AND BETWEEN  
NET ZERO PLATFORMS EUROPE LTD. AND MR. BRIAN RAIVO**

IP, including by not limited to raw materials, labor, manufacturing expenses, reasonable and customary expenses, taxes, duties, and levies imposed on the revenue, and any returns, discounts, allowances or credits granted to customers.

4.2 Royalty payments shall be made quarterly, within 30-days of the end of the calendar quarter where the Buyer has generated Net Revenues based on completion of management accounts by a qualified accountant.

**5. Confidentiality**

5.1 The Seller agrees to maintain the confidentiality of all Buyer information received during the negotiation and execution of this Agreement for a period of five (5) years.

**6. Governing Law**

6.1 This Agreement shall be governed by and construed in accordance with the laws of England. This is essential given the lead customer for the Buyer is in the United Kingdom. It is agreed that when a United States of America (USA) based customer emerges the Buyer will assign this Agreement to Net Zero Platforms LLC (a USA-based company) for USA-based Net Revenues and transfer of the governing law to the State of Tennessee.

**7. Entire Agreement**

7.1 This Agreement, together with its exhibits, constitutes the entire agreement between the Parties with respect to the subject matter hereof and supersedes all prior agreements, understandings, negotiations, and discussions, whether oral or written, of the Parties.

 BR

**SALES PURCHASE AGREEMENT  
BY AND BETWEEN  
NET ZERO PLATFORMS EUROPE LTD. AND MR. BRIAN RAIVO**

IN WITNESS WHEREOF, the Parties have executed this Sales Purchase Agreement as of the date first above written.

**SELLER:**

Mr. Brian Raivo  
2530 North 26<sup>th</sup> West  
Idaho Falls, Idaho 83402  
208.529.8023 (cell)

Signature: Brian Raivo


Date: 3/15/2024

**BUYER:**

Richard Molsbee  
Net Zero Platforms Europe Ltd  
11 St. Paul's Square  
Birmingham B3 1RB  
865.966.4306 (USA, cell)

Signature: Richard Molsbee

Date: 20 March 2024

 BR

# EXHIBITS

## Exhibit A – Letter of Intent

  
BR

Mr. Brian Raivo

Idaho

September 10<sup>th</sup>, 2023

RE: Letter of Intent for the Purchase of Intellectual Property

Dear Mr. Raivo,

We, offer this letter of intent (LOI) to outline the arrangement between the Buyer and the Seller for patent #10,435,295 *COUPLING AN ELECTRIC FURNACE WITH A LIQUID FUEL SYNTHESIS PROCESS TO IMPROVE PERFORMANCE WHEN PROCESSING HETEROGENEOUS WASTES* and related materials (inclusive "IP").

The LOI includes the following key points:

1. We confirm the intent to purchase the IP after performing due diligence (DD). For this option and in recognition of the conditions below we will pay on signature of this agreement US\$1,000.00 to Mr. Brian Raivo.

The DD exercise is essential to remove the need for onerous conditions on the Sellers related to indemnification.

2. This Agreement pertains exclusively to the Intellectual Property (the "IP") associated with the utilization of the specific technology for the production of liquid fuels through the coupling of gasification and the Fischer-Tropsch process ("FT"). Both Parties acknowledge and agree that any and all other IP, whether related or unrelated to the technology described herein, shall be deemed irrelevant for the purposes of this Agreement. Neither Party shall have any right, claim, or interest in or to such other IP, and each Party hereby waives and releases any and all claims, now known or hereafter known, in connection with such other IP.
3. This LOI will be exclusive between Mr. Brian Raivo, and Mr. Richard Molsbee, a representative of the Buyer, for up to 180 days from the signature of this LOI while the Buyer performs DD, searches and negotiations with other Sellers, who are named on a patent that is part of the IP. DD will be performed at the Buyers cost. The Buyer's understanding is that you have full ownership of the IP apart from the patent that Mr. Tom Eddy co-authors.

The Buyer has the right to access, review and discuss the IP with external parties.

4. The Seller agrees to maintain the strict confidentiality of all buyer information received during business negotiations or transactions associated with the LOI and intended Purchase of the IP. This includes but is not limited to the buyer's name, contact details, financial information, and any other information. The Seller shall not disclose or share such information with any third party without the prior written consent of the Buyer.

This obligation of confidentiality shall remain in effect for three (3) year after the signature of the LOI and the intended Purchase of the IP.

5. It is the intent that, the Buyer would, following successful DD execute the complete Purchase for the IP based on this LOI:

90 BR

312



Mr. Brian Raivo

Idaho

September 10<sup>th</sup>, 2023

- a. This would include an initial payment of US\$12,000.00 on the signature of the Purchase agreement. The Purchase agreement would reflect both this LOI's and the DD results.
- b. In recognition of the above and the importance of the IP and market focus on Sustainable Aviation Fuel (SAF), the Buyer, based on the advantages of the prescribed technology supported by this IP, would provide additional payments to the Seller based on royalties in liquid fuels produced by the Buyer.

SAF markets demand more than 80 million gallons per year of SAF, with more than 100 new projects recently started to produce SAF. Where Buyer secures such a project with the IP, for example, 500,000 gallons per year could generate US\$120,000 per year income based on a 5% royalty.

- c. The royalties at 5% of the net revenue the Buyer invoiced to the customer and paid to the Buyer for liquid fuel quantities produced by the Buyer pertaining to this IP for ten years following the signing of this agreement would be paid to the Seller as royalties.
- d. Royalty payments will be made quarterly on completion of management accounts by a US-qualified accountant. The SAF market is highly regulated, and quantities of fuels intended to be provided by the Buyer would be subject to regulatory scrutiny on quantity and quality by federal authorities. This will assure the Seller of the accuracy of any royalty payments made.

Sincerely,



cc: J.W.  
K.D.

If you agree to this LOI, please sign and date. I will send a check upon receipt of your acceptance.

Signature



Date

9/11/23

BR



# Coupling an electric furnace with a liquid fuel synthesis process to improve performance when processing heterogeneous wastes

**US10435295B2**

United States



Download PDF



Find Prior Art



Similar

**Inventor:** Thomas L Eddy Brian D Rave**Current Assignee :** [United Therapeutics Corporation](#)**Worldwide applications**2016 [US](#)**Application US15/366,600 events** ⓘ

2016-12-01 • Application filed by Individual

2016-12-01 • Priority to US15/366,600

2018-06-07 • Publication of US20180155190A1

2019-10-08 • Application granted

2019-10-08 • Publication of US10435295B2

**Status** Active - Reinstated

2037-05-30 • Adjusted expiration

**Info:** Patent citations (9) Cited by (5) Legal events  
Similar documents Priority and Related Applications**External links:** [USPTO](#) [USPTO PatentCenter](#) [USPTO Assignment](#) [Espacenet](#) [Global Dossier](#) [Discuss](#)

BR

**Abstract**

(12) **United States Patent**  
**Eddy et al.**

(10) **Patent No.:** **US 10,435,295 B2**  
(45) **Date of Patent:** **Oct. 8, 2019**

(54) **COUPLING AN ELECTRIC FURNACE WITH  
A LIQUID FUEL SYNTHESIS PROCESS TO  
IMPROVE PERFORMANCE WHEN  
PROCESSING HETEROGENEOUS WASTES**

(71) Applicants: **Thomas L Eddy**, Naples, FL (US);  
**Brian D Raivo**, Idaho Falls, ID (US)

(72) Inventors: **Thomas L Eddy**, Naples, FL (US);  
**Brian D Raivo**, Idaho Falls, ID (US)

(\*) Notice: Subject to any disclaimer, the term of this  
patent is extended or adjusted under 35  
U.S.C. 154(b) by 180 days.

(21) Appl. No.: **15/366,600**

(22) Filed: **Dec. 1, 2016**

(65) **Prior Publication Data**

US 2018/0155190 A1 Jun. 7, 2018

(51) **Int. Cl.**  
**C01B 3/34** (2006.01)  
**C10G 2/00** (2006.01)

(52) **U.S. Cl.**  
CPC ..... **C01B 3/34** (2013.01); **C10G 2/32**  
(2013.01); **C01B 2203/0216** (2013.01); **C01B**  
**2203/0222** (2013.01); **C01B 2203/062**  
(2013.01); **C01B 2203/085** (2013.01); **C01B**  
**2203/0861** (2013.01); **C10G 2300/4081**  
(2013.01); **Y02E 50/32** (2013.01)

(58) **Field of Classification Search**  
CPC ..... **C02F 3/02**  
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

5,541,386 A *	7/1996	Alvi .....	A62D 3/19
			110/236
5,666,891 A *	9/1997	Titus .....	A62D 3/19
			110/250
6,204,427 B1 *	3/2001	Eddy .....	F23G 5/085
			110/346
8,237,006 B2 *	8/2012	Stone .....	C10J 3/00
			588/321
8,764,875 B2 *	7/2014	Huang .....	C01B 3/50
			585/240
2008/0182298 A1 *	7/2008	Day .....	C01B 3/22
			435/72
2013/0333288 A1 *	12/2013	Richley .....	C10K 3/003
			48/113
2014/0175335 A1 *	6/2014	Anderson .....	C10J 3/18
			252/373
2016/0023928 A1 *	1/2016	Chung .....	B09B 3/00
			71/9


\* cited by examiner

Primary Examiner — Nina Bhat

(57) **ABSTRACT**

An improved method for processing heterogeneous municipal solid waste, biomass and even construction and demolition waste into liquid hydrocarbon fuels and chemicals is obtained by coupling the synthesis process with an electric furnace. The furnace separates the metals and inorganics from the organic materials. The high temperatures gasify the organics into a relatively clean syngas after particulate and acid gas removal. The yield is increased above that expected from the feedstock by the addition of waste effluents from the synthesis process, such as CO<sub>2</sub>, H<sub>2</sub>O and possibly tail gas constituents. The recycled effluents are heated by the syngas being quenched in heat exchangers. Excess high pressure effluents are also heated by the syngas for power generation via gas or steam turbine generators. The optimum concentration of added effluents and heat exchanger configurations are determined by novel methods for maximum yield, energy efficiency and minimum carbon footprint.


**13 Claims, 4 Drawing Sheets**



Electric furnace in submerged arc furnace (SAF) configuration.

An improved method for processing heterogeneous municipal solid waste, biomass and even construction and demolition waste into liquid hydrocarbon fuels and chemicals is obtained by coupling the synthesis process with an electric furnace. The furnace separates the metals and inorganics from the organic materials. The high temperatures gasify the organics into a relatively clean syngas after particulate and acid gas removal. The yield is increased above that expected from the feedstock by the addition of waste effluents from the synthesis process, such as CO<sub>2</sub>, H<sub>2</sub>O and possibly tail gas constituents. The recycled effluents are heated by the syngas being quenched in heat exchangers. Excess high pressure effluents are also heated by the syngas for power generation via gas or steam turbine generators. The optimum concentration of added effluents and heat exchanger configurations are determined by novel methods for maximum yield, energy efficiency and minimum carbon footprint.

Images (5)



Classifications

■ C10G2/32 Production of liquid hydrocarbon mixtures of undefined composition from oxides of carbon from carbon monoxide with hydrogen with the use of catalysts

Claims (13)

Hide Dependent ^

Handwritten signature and the text "B12".

We claim:

1

# COUPLING AN ELECTRIC FURNACE WITH A LIQUID FUEL SYNTHESIS PROCESS TO IMPROVE PERFORMANCE WHEN PROCESSING HETEROGENEOUS WASTES

## CROSS-REFERENCE TO RELATED APPLICATIONS

This application claims the benefit of U.S. provisional application Ser. No. 62/266,582 filed Dec. 12, 2015, the disclosure of which is hereby incorporated in its entirety by reference herein.

## FEDERALLY SPONSORED RESEARCH

None

## SEQUENCE LISTING

None

## BACKGROUND

Prior Art—U.S. Patents

Prior Patents Indicating Recycling from Synthesis Unit to a Partial Oxidation Gasifier, Reformer, Autothermal Reformer, or Equivalent.

Chang, et al. (U.S. Pat. No. 4,138,442; 1979) starts with a syngas from fossil fuels that is converted by catalyst to a mix of methanol and DME. The DME is converted with a zeolite catalyst to product containing gasoline and a light hydrocarbon gas fraction. The latter could be liquefied, releasing a hydrogen gas that could be recycled to the fossil fuel conversion or otherwise used.

Iijima (U.S. Pat. No. 6,489,370; 2002) uses steam mixed with natural gas to generate a syngas in a reformer heated by radiation from a separate combustion unit. Carbon dioxide from the combustion unit is added to the steam-natural gas mixture into the reformer to generate more carbon monoxide. The unit acts as a partial oxidation reformer, but with indirect heating so that air can be used as the oxidant.

Thiebaut (U.S. Pat. No. 6,846,951; 2005) recycles 5-50% of the carbon dioxide from a reformer and fed with a natural gas feedstock and oxygen into an autothermal reformer in a process to make methanol and acetic acid.

Fenouil, et al. (U.S. Pat. No. 7,250,450; 2007) uses a gaseous hydrocarbon feedstock in a partial oxidation process to make a syngas fed to a catalytic converter. The resulting hydrocarbon products are separated from a recycle stream. Carbon dioxide is then separated out from the recycle stream before recycling the carbon dioxide depleted stream into the partial oxidation unit.

Gueh (U.S. Pat. No. 8,513,316; 2013) presents ideas of mixing carbonaceous feedstock with recycled carbon dioxide and tail gas from FT synthesis to feed a thermal conversion plant or a chemical conversion plant to generate a syngas. The thermal conversion plant consists of a molten metal bath heated externally. The ideas are not supported by any data or details on how to accomplish the proposed methods.

Ravikumar, et al. (U.S. Pat. No. 8,629,188; 2014) proposes a gas to liquids plant in which energy for natural gas reformation is provided at least in part by biomass (shale oil) gasification. A hydrocarbon feed stream is provided to a reformer and a second biomass feed stream partially oxidized. The latter is partly fed to a burner for the reformer energy and then the balance combined with the first feed

2

stream to be synthesized in a Fischer-Tropsch process or equivalent into a liquid fuel product. Carbon dioxide in the product stream is redirected to the reformer. The water effluent is separated into a waste water that is combined with the first feed stream and into a purge stream, a portion of which is fed to a turbine to generate power, the exhaust energy of which is recycled to the reformer.

Blevins, et al. (U.S. Pat. No. 8,936,769; 2015) produce a syngas from a mix of steam and carbonaceous material in a reformer. A catalytic conversion unit then generates a hydrocarbon product stream from which a tail gas is separated of carbon monoxide, carbon dioxide, hydrogen and methane. Tail gas options include possible fluid flows to various system components such as a mixing apparatus, a reformer, and/or catalytic synthesis conversion unit.

Prior Patents Indicating Recycling from a Synthesis Unit Back to a Synthesis Unit (a Common Way to Increase the Carbon Conversion Efficiency for a Given Catalyst) or Equivalent.

Janda (U.S. Pat. No. 6,444,712; 2002) proposes a methanol synthesis unit and a hydrocarbon synthesis unit to generate methanol and hydrocarbon products from natural gas. Carbon dioxide from the hydrocarbon synthesis unit is separated out and mixed with natural gas to obtain an optimal syngas composition to the separate methanol synthesis unit.

Price (U.S. Pat. No. 6,740,683; 2004) synthesizes chemicals from syngas. Uses hydrogen-poor hydrocarbons with  $H_2/CO < 2$ , but recycles vapor product from the FT synthesis process to obtain  $2 < H_2/CO < 3$  (a typical FT synthesis recycle technique).

Early (U.S. Pat. No. 7,790,775; 2010) presents complex methods of recycling syngas and FT synthesis products streams to the synthesis process to increase carbon conversion efficiency.

Severinsky (Patents U.S. Pat. No. 7,641,292; 2010, U.S. Pat. No. 8,114,916; 2012 and U.S. Pat. No. 8,168,143; 2012) presents methods of recycling syngas and FT synthesis products streams to the synthesis processes to increase carbon conversion efficiency.

Menzel (U.S. Pat. No. 8,741,971 B2; 2014) discusses a method and system for operating a Fischer-Tropsch synthesis from coal gasification for production of feed gas of CO and hydrogen. The gas is desulphurized and fed to the Fischer-Tropsch system for the production of liquid products. The CO and CO<sub>2</sub> gas exiting the FT process is compressed and fed to a converter stage in which the CO is converted with steam into H<sub>2</sub> and CO<sub>2</sub>. The CO<sub>2</sub> is subsequently removed and the H<sub>2</sub> enriched gas is recycled along with primary de-sulphurized gas back to the FT process. Advantage is seen in reduced de-sulphurizing costs and increased H<sub>2</sub> content of the gas entering the FT plant.

Prior Patents Indicating a Separation but No Recycling for Synthesis, or Equivalent.

Bohn, et al. (U.S. Pat. No. 6,306,917; 2001) use a partial oxidation process to generate a syngas from a hydrocarbon feedstock. After FT synthesis, the CO<sub>2</sub> is separated out as a product (not recycled to system) and the remaining hydrogen rich tail gas used in a gas turbine to generate power.

Prior Patents Using External Sources of Carbon Dioxide  
Shiroto, et al. (U.S. Pat. No. 6,656,978; 2003 and U.S. Pat. No. 6,806,296; 2004) uses lower hydrocarbon numbers and an external source of carbon dioxide mixed with steam. A special catalyst produces a syngas with a carbon conversion efficiency of at least 50%. If the syngas molar  $H_2/CO$  ratio is 1.5 to 2.5, syngas is reacted in a FT catalyst process to generate liquid oil. If  $0.5 < H_2/CO < 1.5$ , react with catalyst to synthesize methanol or DME.

O'Rear (U.S. Pat. No. 6,774,148; 2004) blends final syngas from two syngas sources. First source is from a partial oxidation reaction of methane and oxygen to get  $H_2/CO > 2$ . Second source is from LPG and external carbon dioxide to synthesize a syngas of  $H_2/CO > 1.5$ .

Wolf (U.S. Pat. No. 7,960,441; 2011) combines carbon dioxide from combustion and hydrogen from electrolysis in a high temperature system to generate a syngas prior to conversion to hydrocarbon fuels.

Shulenberg et al. (U.S. Pat. No. 8,198,338 B2; 2012) discusses the production of high octane fuel from carbon dioxide and water. Feedstock consists of industrial carbon dioxide and water with the consumption of electricity to drive the process. End products include high octane gasoline, high cetane diesel, or other liquid hydrocarbon mixtures. The process primarily depends on the electrolysis of water into hydrogen and oxygen for initiation. Secondary processes include mixing of hydrogen with  $CO_2$  to optimize the conversion of  $CO_2$  to CO, mixing of hydrogen with CO to produce syngas for conversion to methanol or other hydrocarbons, synthesis of methanol, conversion of methanol to dimethyl ether (DME), conversion of DME to gasoline, conversion of DME to diesel, synthesis of gasoline directly from methanol, and synthesis of DME from syngas.

Surma et al. (U.S. Pat. No. 8,685,121 B2; 2014) discusses the processing of heterogeneous feedstocks including organic and inorganic material in a gasification/vitrification unit. The process includes a downdraft gasifier coupled to a vitrification unit which is then further coupled to a thermal residence chamber. Feedstocks are introduced into the gasifier and mechanically transferred downward with the volatile and non-volatile fractions exiting the gasifier vertically downward through a grated port into a high temperature joule heated vitrification unit. The vitrification unit is controlled at a higher temperature than the gasifier for further processing of the non-volatile fraction into a molten glass product, and the volatile fraction further processes in the vitrification headspace via exposure to plasma from torches or electrodes. The volatile fraction exiting the vitrification unit to a downstream thermal residence chamber operated at a third temperature. The gasification process utilizes oxidants in the form of pure oxygen (90-99% pure), air, carbon dioxide, oxygen enriched air, steam or a combination thereof to maintain a reducing environment for the production of high quality syngas.

#### Other References

METSIM pyrometallurgical software. Proware, Tucson, Ariz.

Zennaro, et al., Syngas: The Basis of Fischer-Tropsch chapter, p. 38, Greener Fischer-Tropsch Processes, P. M. Maitliss & A. de Klerk, Eds., Wiley-VCH, Weinheim, Germany, 2013.

DOE 2000 report: Natural Gas to Liquids Conversion Project, Raytheon Engineers & Contractors, DOE Report 2000-1032585, 2000.

M. McKellar, et al., Aspen Process Model for the Misty Mountain Resource Recovery Plant, INL TAP Report INL/LTD-15-36850, October 2015.

Miglio, Zennaro and de Klerk, Environmental Sustainability chapter, p 329, Greener Fischer-Tropsch Processes, P. M. Maitliss & A. de Klerk, Eds., Wiley-VCH, Weinheim, Germany, 2013.

#### Discussion of Issues

The processing of heterogeneous waste materials, such as municipal solid waste (MSW) or construction and demolition waste (C&D), into a syngas of  $H_2$  and  $CO_2$  for conversion to liquid fuels is difficult by combustion meth-

ods. The variability in flammability and heats of combustion, as well as inorganic content and inertness makes these wastes difficult to burn, as well as trying to partially oxidize properly to a syngas, without sorting organic materials out from metals and inorganic (soil, glass, bricks, ash, etc.) materials.

The utilization of the Fischer-Tropsch catalytic synthesis (FTS) of hydrocarbon liquid fuels (HCLF) has focused on converting natural gas/methane or coal. Various forms of partial-oxidation are employed to obtain the energy for high temperatures required for gasification to a syngas of CO and  $H_2$  and to limit formation of  $CO_2$  and  $H_2O$ . Pure oxygen and steam are usually added to make up deficiencies of oxygen and hydrogen in feedstock. Traditional preference is to obtain a molar  $H_2/CO$  ratio of 2 or larger so that in the FTS, oxygen released from CO joins with excess  $H_2$  to make a waste effluent of water, rather than  $CO_2$ . If insufficient  $H_2$  is introduced,  $CO_2$  is formed as a waste effluent, thus reducing the HCLF yield by reducing carbon conversion efficiency.

A result is that focus of partial-oxidation generation of syngas has been on adding pure oxygen and/or steam to various feedstocks of  $CH_4$ , coal, biomass or MSW. This is a major issue for heterogeneous wastes because of the added amount of additives that must be added to obtain  $H_2/CO > 2$ , and the energy required to disassociate these additives toward gasification.

Another issue is that biomass (wood chips, etc.), MSW and C&D wastes have lower heats of combustion making it difficult to reach gasification temperatures with partial-oxidation requirements on CO and  $H_2$ . Lower temperatures produce more complex hydrocarbon species that complicate the downstream cleanup process for the FTS.

A third issue is that biomass and MSW contain various amounts of moisture which lower the heat of combustion and temperatures even further, if not dried. Drying requires additional energy. If dried, steam needs to be added later to provide for the deficiency of hydrogen in waste requiring more energy input.

A fourth issue is that whereas biomass may be relatively homogenous, MSW and C&D wastes are not, containing organic material, inorganic material and metal. In a partial-oxidation process the organic materials need to be pre-sorted out to make the syngas.

Fifth, the heterogeneous nature of the MSW and C&D wastes makes it difficult to control the partial-oxidation process temperatures and reactions in the reaction chamber to obtain a consistent syngas composition with a minimum of undesirable hydrocarbon species.

A sixth issue is that there is always some ash generated. Temperatures from partial-oxidation methods are insufficient to obtain a molten, homogenous ash or slag that can be used to produce value-added construction products, rather than aggregate. The same temperature constraints can be said for any metal waste in the feedstock, reinforcing the need for sorting.

Syngas generation methods considered have usually been a form of partial-oxidation methods, the variations of which will be considered as one here. An alternative gasification method is by using electric furnace methods, using a variety of plasma torch melter (PTM) or graphite-electrode arc melter (GAM) furnaces. The focus of this work is on a form of the electric arc furnace (EAF) or GAM called a submerged arc furnace (SAF) with which the electrodes are immersed into the molten slag in the furnace for optimum performance.

An issue with the electric furnace process is cost of electricity compared to cost of partial combustion with pure oxygen. This would be a major factor if one follows the conventional practice of adding steam and other additives to raise the molar  $H_2/CO > 2$  in the syngas for those wastes having  $H_2/CO$  ratio near unity. Economic studies have shown that processing of MSW in a SAF compensates for the electricity costs by way of revenues from value-added products. The SAF processes are competitive if not more economic than other processes for waste-to-energy plant sizes larger than 500 tonnes/day.

Of the prior art U.S. patents, only the first section on recycling additives into a gasifier, reformer or similar unit prior to a synthesis conversion unit appears to be comparable to the embodiments proposed here. Most of those employ partial oxidation methods which are not used herein because of the heterogeneous nature of the feedstock. When  $CO_2$  is added to the process it is usually because the main feedstock is natural gas with an abundance of hydrogen so that the water gas shift can be used at lower temperatures to shift  $CO_2 + H_2$  to  $CO$  and  $H_2O$  to give more carbon monoxide for conversion in the synthesis process. Many of the processes adding  $CO_2$  were generating alcohols that contain the OH radical and can utilize the additional oxygen from  $CO_2$ .

The most similar patent to this is that of Gueh (U.S. Pat. No. 8,513,316; 2013) that mixes  $CO_2$  and tail gases from a FT synthesis with a carbonaceous feedstock and passes the mixture through a molten metal bath as a medium to obtain a syngas without any discussion of compositions or thermal conditions. The metal must have a relatively low melting temperature to be melted by an external source in the marine vehicle, too low a temperature to melt the ash contained with the carbonaceous feedstock, unless it is a gaseous feedstock. It appears impossible if not impractical to do what the author proposes from the patent description which is not documented by any data. The present embodiment uses a molten slag/ash to assist in the gasification process and processes the additives within the system to get maximum benefit from their capabilities.

#### Advantages

A Prior work (U.S. Pat. No. 6,204,427, CA 2274540) discusses a process and apparatus (P&A) that can separate the metal and inorganic materials from the organic materials, and from organic materials produce a syngas to generate liquid fuels in a FTS process. This prior work is the basic P&A on which the proposed embodiment is an extension. The proposed embodiment couples prior P&A to a FTS process in such a way as to compliment each other. Compared to partial-oxidation methods for MSW, C&D and biomass wastes, advantages of the coupled SAF-FTS are:

- To generate a cleaner syngas with less complex hydrocarbon species.
- To reduce external input-energy requirements.
- To increase energy efficiency of the coupled systems.
- To increase the HCLF yield above that from the input feedstock alone.
- To increase the internal recycling of process effluents.
- To decrease the carbon footprint.
- To resolve the presented issues of the partial-oxidation methods for heterogeneous waste.

#### SUMMARY

##### Related Prior Patent Features

The present embodiment is built on and complementary to prior work by the inventors, including a unique SAF design

process & apparatus configuration, to be referred to as "Process and Apparatus" (P&A), (U.S. Pat. No. 6,204,427, CA 2274540), a start-stop tapping device (U.S. Pat. No. 6,299,830) to tap high-temperature molten slag and metal into containers, and a rotating electrode drive mechanism (U.S. Pat. No. 5,914,979) to facilitate electrode operating gaps, tapping, and arc starting without a conducting medium.

The said P&A system previously patented, states the detailed design and operational methods that are available to be used here. In brief, The MSW or other waste material is shredded and fed into the submerged arc furnace. The SAF is divided into three (3) regions: the melt pot on the bottom, the psi region above the pot which has different refractory and a number of ports, and the reactor, gasifier or thermal oxidizer (in other applications) above the psi to provide residence time to complete gasification. Metal in the waste is melted at  $>1600^\circ C$  and its phase sinks to the bottom of the pot, to be tapped into ingots when appropriate. Inorganics are melted at  $>1600^\circ C$ , are immiscible with the metal, and rest above the metal in the pot.

The MSW and its organics are fed into the side of the pot/psi, creating a predominantly organic cold top at  $1300^\circ C$  or higher, sitting on top of the slag. The organics in the cold top are pyrolyzed and ultimately gasified. The power is input through two DC (or 3 AC) graphite electrodes sticking down through the cold top just into the molten slag, which is electrically conducting when heated to over  $1400^\circ C$ . The pot is highly insulated with high-temperature ruby refractory or equivalent next to the slag and a lighter, better insulator between the ruby and the steel shell. The thicknesses of the refractory layers are such as to cool the slag near the walls to develop a skull of slag to preclude wear of the refractory. There is no water cooling of the walls.

The purpose of the psi region is to continue the pyrolyzation of the organics and provide usually 8 ports (an octy-psi) for the electrode drives, pin-hole camera, an auto-darkening camera, other diagnostic instruments, and a manual access port. The psi region is insulated with two different layers of lighter insulation than the pot, to reduce heat losses and maintain gasification temperatures.

A narrower constrictor duct leaves the psi to the gasifier region to reduce carryover from the cold top. The gasifier is an extension to provide more residence time for the gasification reactions to be completed at high temperature. Neither the p or gasifier regions are water cooled in order to reduce heat transfer through their walls.

Following the SAF is one of several typical air pollution control type systems to clean up the offgas or syngas. It can be a water spray quench to rapidly cool the syngas to preclude reformation of hydrocarbons, followed by an acid gas scrubber and then a bag-house filter system.

The present embodiment opted for crossflow heat exchangers to cool the syngas to below  $200^\circ C$  so that a baghouse filter system can collect the particulate before the scrubber. A water-wall heat exchanger may replace the first crossflow heat exchanger.

After the cleanup system the syngas is cooled, compressed to the pressure to be used in the FT process and temporarily stored in tanks until used.

A commercial FT synthesis and refinery process (FTP) further cleans up the acid gases to the FT requirements and performs the various processes needed to produce the desired liquid fuel products and chemicals.

##### 65 New Patent Features

The novelty of the embodiment is that the waste  $CO_2$ , water and possibly the tail gas effluents from the selected FT

system are recycled, first as coolants to the syngas, second to produce power from the energy so obtained (as also done by others), and then an appropriate amount of CO<sub>2</sub> and steam therefrom are reheated and injected into the SAF to enhance the yield from the Feedstock, as well as to reduce the electrical energy required to the SAF. CO<sub>2</sub> and H<sub>2</sub>O effluents from the FT system that are not used as additives to the SAF are also heated by the syngas and used in CO<sub>2</sub>-gas and steam turbines to cogenerate electricity to reduce the net required by the SAF.

The amount of recycled CO<sub>2</sub> and steam from the FT system is critical to maximize the yield, minimize the cost, and provide the simplest and most robust compositions. This is called the optimum case. In the present embodiment, the optimum case is determined by running perturbations of different CO<sub>2</sub>, H<sub>2</sub>O, CH<sub>4</sub> and O<sub>2</sub> concentrations as additives through a pyrochemical software model (METSIM by Proware). The resulting equilibrium syngas concentrations were input to a FT Products model developed for the purpose and based on test results. The perturbations with the highest yield, lowest cost and most recycling of additives were selected for the optimum case. Perturbations of approximately 20% of the optimum values give similar results showing the robustness of the embodiment. The result without additives gives a much inferior result. The optimum result may vary depending upon the FT system effluent concentrations.

In the present embodiment, approximately 1/3 of the CO<sub>2</sub> and 1/3 of the H<sub>2</sub>O generated by the FT system are recycled to the SAF, thus reducing the carbon (and water) footprint. With the additives as determined, the yield from the MSW is increased considerably over what it would be without the additives or what would result from a partially oxidized method. The net electricity required for the SAF is reduced by more than 10%.

The novelty of the energy recovery over traditional methods is 1) heating of waste products from the FTP by the syngas to be injected into the SAF as additives to improve conversion efficiency to liquid fuels and 2) heating of waste products from the FTP by the syngas to higher temperatures to produce electric power via gas and steam turbines. A corollary of the above is using the waste products from the FTP products to rapidly cool (quench) the syngas to inhibit reformation of hydrocarbons prior to preparation for the FT synthesis. The use of a SAF gasifier enables the recycling of FT synthesis energy and mass flows in a novel, advantageous manner, not just utilizing waste energy to heat water to steam for power.

#### BRIEF DESCRIPTION OF THE DRAWINGS

Figures depicting the details of the embodiment and to the structures to which is attached are on the accompanying diagrams, as well as photos of the associated test facility. Reference numerals throughout the various FIGURES denote like elements.

FIG. 1 a representation of an electric furnace in the SAF form.

FIG. 2 flow diagram of the basic elements.

FIG. 3 SAF drawing with gasifier to heat exchangers for 500 tonne/day of MSW.

FIG. 4 photographs of a related electric furnace test facility.

#### DRAWINGS—REFERENCE NUMERALS

- 1 Waste feedstock into submerged arc furnace (SAF)
- 2 Hopper

- 3 Molten metal
- 4 Molten slag
- 5 Recycled steam from FT process
- 6 Recycled CO<sub>2</sub> from FT Process
- 7 Shredder, compactor, feeder components
- 8 Electric furnace in SAF configuration
- 9 Molten or temporarily partially-solidified metal
- 10 Molten slag
- 11 Cold top of feedstock, partially processed
- 12 Graphite electrodes (2).
- 13 Offgas to gasifier
- 14 Constrictor
- 15 Reactor to complete gasification
- 16 Syngas
- 17 Heat exchanger HX1—syngas to low pressure CO<sub>2</sub> for SAF
- 18 CO<sub>2</sub> gas turbine—after reheat process
- 19 Heat exchanger HX2—syngas to medium pressure CO<sub>2</sub>
- 20 CO<sub>2</sub> gas turbine—CO<sub>2</sub> before reheat process
- 21 Heat exchanger HX3—syngas to high pressure CO<sub>2</sub>
- 22 Heat exchanger HX8—syngas to medium pressure for SAF
- 23 H<sub>2</sub>O Steam turbine—with takeoff for reheating SAF steam
- 24 Steam condenser
- 25 Condensate water pump
- 26 Heat exchanger HX9—syngas to FTP waste water recycle
- 27 Heat exchanger—syngas to separate Rankine cycle steam
- 28 Steam turbine for separate Rankine cycle
- 29 Steam condenser
- 30 Water pump to raise condensate to high pressure for separate Rankine cycle
- 31 Boiler to boil water from scrub water waste heat
- 32 Filter baghouse to collect particulate to recycle to SAF
- 33 Acid-gas scrubber
- 34 Rectisol or equivalent S-cleanup system
- 35 Sulfolin or equivalent S-recovery process
- 36 CO<sub>2</sub> for blanket gas in input materials handling
- 37 Sulfur for recycling
- 38 A naphtha liquid refinery
- 39 Chemical products
- 40 Fuel products
- 41 Fe-LTFT (low temperature, Fischer-Tropsch) catalytic process
- 42 Gases
- 43 Benfield or equivalent process
- 44 Tail gas
- 45 CO<sub>2</sub> to be recycled
- 46 Oil product & waxes
- 47 Aqueous product including alcohols
- 48 Fischer-Tropsch refinery
- 49 Chemical products
- 50 Fuel products
- 51 FTP waste water for recycling
- 52 Outline of a simplified commercial Fischer-Tropsch synthesis & refinery system
- 53 Particulate collected
- 54 Scrub water cooler
- 55 Scrub water blowdown to recover salts
- 56 Compressor
- 57 Storage tank



## Description

The Prior work (U.S. Pat. No. 6,204,427, CA 2274540), on which this work is an extension, utilizes an electric furnace, in the form of a submerged arc furnace (SAF) configuration to simplify the operation because the SAF separates the metal and inorganics from the organics by melting the former into the bottom of the melt pot and pyrolyzing and gasifying the organic materials. The concentrated energy density of the SAF heats the materials to sufficiently high temperatures to tap out the metal into ingots for recycling, tap and cast the inorganics into construction products, and pyrolyzing and gasifying the organics into a syngas (without oxidation) for use in a Fischer-Tropsch synthesis and refining process (FTP) to generate liquid fuels and chemicals.

The FT process is very exothermic and operates at high pressure many times atmospheric pressure. A low temperature FTP with iron-based catalyst (Fe-LTFT) operates approximately between 230-240 C and a high-temperature process (Fe-HTFT) at 320-330 C and pressures usually of 15 to 25 atmospheres. The FTP waste water and CO<sub>2</sub>, as well as some other tail gases are output under these temperature and pressure conditions. Some commercial systems utilize this waste heat in various ways, such as for driving low temperature turbines, for drying, or for other lower temperature heating applications. In the present patent, these FTP H<sub>2</sub>O and CO<sub>2</sub> wastes are heated to much higher temperatures and recycled to the gasification process. The excess CO<sub>2</sub> and H<sub>2</sub>O beyond recycling needs are also heated to higher temperatures and used in gas and steam turbines to generate system power. The source of the energy recycled comes from both the FT synthesis process and from the syngas cooling required prior to the clean-up and feeding to the FTP.

The four main thrusts for Fischer-Tropsch synthesis to liquid fuel generation can be expressed as XTL where X is the feedstock. GTL is (natural) gas to liquid, CTL is for coal, BTL is for biomass and WTL for waste such as Municipal solid (MSW) waste. XTL systems can be separated into subsystems such as 1) syngas generation, 2) syngas cooling and heat recovery, 3) syngas clean-up, and 4) the Fischer-Tropsch conversion and refining systems.

The molar ratio of H<sub>2</sub>/C in most hydrocarbon liquids (diesel, gasoline, not alcohols) is approximately 1.1. For methane/natural gas, molar H<sub>2</sub>/C=H<sub>2</sub>/CO=2; therefore, an excess of H<sub>2</sub>, which is used to remove the excess oxygen in the FT synthesis as water. For bituminous coal, H<sub>2</sub>/C is about 0.8; therefore, one would have to add a considerable amount of steam to convert all the excess oxygen back into water after FTS. An alternative, is to add only enough hydrogen to get the H<sub>2</sub>/CO ratio to 1.1 so that all the C in the syngas CO has the potential to be converted to hydrocarbon compounds. The excess oxygen from the FT synthesis is then removed by CO into CO<sub>2</sub>. This reduces the yield of liquid fuels because there is less CO to react in the FT process. Traditional methods with coal, biomass or MSW that require H<sub>2</sub>/CO<2.0 add oxygen and steam to get the syngas H<sub>2</sub>/CO up to or over 2 in order to get the oxygen removed from CO to predominantly H<sub>2</sub>O. The energy comes from the partial combustion that also produces some CO<sub>2</sub> and H<sub>2</sub>O and reduces the yield somewhat. If electric gasification is used with traditional reaction compositions, the pyrolysis and gasification can require more energy than necessary when a different philosophy (electrical heating) is employed.

The two most common FTS processes are with iron (Fe) or cobalt (Co) catalysts. Iron catalysts can activate the water gas shift (WGS), CO+H<sub>2</sub>O→H<sub>2</sub>+CO<sub>2</sub>, at the FTS temperatures used to increase H<sub>2</sub> and the H<sub>2</sub>/CO ratio, but at a cost of converting CO to CO<sub>2</sub>. Cobalt catalysts do not activate that WGS reaction. Whether CO is reduced by the WGS or by a direct conversion of CO to CO<sub>2</sub> in the FT reactor appears to be a moot point, because the carbon conversion efficiency is reduced a similar amount with either method. The direct method is preferred here because the SAF syngas temperatures result in very small concentrations of H<sub>2</sub>O and CO<sub>2</sub>, and the process is not dependent on the WGS so either Fe- or Co-FTS can be used.

## Performance Parameters

A parameter significant to the gasification process is the molar C/O ratio of the input feed and any additives. The C/O ratio needs to be very close to unity in order to maximize the CO from the carbon in the feedstock. Otherwise the process would form either CO<sub>2</sub> if excess O<sub>2</sub> is available or free carbon if the O<sub>2</sub> is deficient.

Another parameter used to indicate performance of XTL processes is the carbon or conversion Efficiency. The C-efficiency can be applied to the syngas generation, the FTS conversion, or the overall system. For the syngas generation, it is the molar ratio of CO generated to the carbon in the feedstock. For the FT conversion, a practical C-efficiency would be the ratio of C in the liquid fuels compared to the CO in the syngas. An overall C-efficiency would then be the molar ratio of the carbon in the liquid fuel generated divided by the carbon in the feedstock.

A third parameter used is the molar ratio of H<sub>2</sub>/CO (which also equals the molar H<sub>2</sub>/C). There are several different processes from feedstock to FT syncrude for which the H<sub>2</sub>/CO ratio can be specified:

The feedstock input H<sub>2</sub>/CO ratio (with or without moisture).

The "fresh" syngas H<sub>2</sub>/CO ratio generated from the gasification system.

The inlet syngas to the FT system which may be a mixture of fresh and recycled syngas.

The exit or recycled syngas H<sub>2</sub>/CO ratio usually from the tail gases separated from the liquid fuels, waxes, CO<sub>2</sub> and water exiting the FT system.

The carbon conversion efficiency discussed above will also affect the H<sub>2</sub>/CO ratios along the flow streams.

Consider the input H<sub>2</sub>/CO ratios for the different XTL. For GTL with G=CH<sub>4</sub>, the feedstock H<sub>2</sub>/CO ratio is 2, but partial oxidation methods usually generate CO<sub>2</sub> and H<sub>2</sub>O in the syngas; hence, the GTL syngas H<sub>2</sub>/CO is usually less than 2 and the carbon efficiency is less than 100%; therefore, GTL systems try for H<sub>2</sub>/CO~2.15.

For CTL with coal assumed to be fixed carbon (char), H<sub>2</sub>/C is about 0.7; but for an Eastern bituminous coal, H<sub>2</sub>/C may be 0.8 or higher. A BTL biomass of approximate chemical composition of C<sub>6</sub>H<sub>9</sub>O<sub>4.2</sub> (excluding moisture), H<sub>2</sub>/C would be 0.75, but with moisture could be 1.5 or higher. A typical WTL MSW with an average composition of C<sub>6</sub>H<sub>10</sub>O<sub>3</sub> would be 0.83 but as high as 1.5 including associated moisture. The organic formulas have been expressed in the form of cellulose, C<sub>6</sub>H<sub>10</sub>O<sub>5</sub>, for consistency.

With CH<sub>4</sub>, there is a "natural" excess of H<sub>2</sub>, so it is convenient to carry away the oxygen freed from the CO in the FTP as H<sub>2</sub>O. The electrical pyrolysis/gasification methods do not use oxidation methods and create sufficiently high temperatures to minimize the CO<sub>2</sub> and H<sub>2</sub>O in the syngas, which can then have the same H<sub>2</sub>/CO ratios as in the


## 11

feedstock. The oxygen freed from the CO can then be carried away by CO as CO<sub>2</sub> instead of the deficient H<sub>2</sub>. This would reduce yield, unless one adds CO<sub>2</sub> to generate more CO. The H<sub>2</sub>/CO variations will be discussed in more detail below.

Most of the XTL Research and Development has been with GTL, followed by CTL, with some for BTL, and very little with WTL. The last is probably because the WTL waste is more heterogeneous. Compositions vary widely and are not amenable to partial oxidation for gasification without sorting and sizing. In the following, simple examples of the gasification and FT processes are discussed to show the novel differences between the partial oxidation and electric gasification processes.

#### GTL Example with Partial Oxidation for Gasification

Zennaro, et al. (Syngas: The Basis of Fischer-Tropsch chapter, p. 38, Greener Fischer-Tropsch Processes, P. M. Maitliss & A. de Klerck, Eds., Wiley-VCH, Weinheim, Germany, 2013) provides the GTL reactions using partial oxidation for syngas generation. The overall reaction can be written as:



where the single H<sub>2</sub> has been combined with an alkene (C<sub>n</sub>H<sub>2n</sub>) to make an alkane (C<sub>n</sub>H<sub>2n+2</sub>) and the C<sub>7</sub> formulas represent the several alkenes and alkanes (of higher and lower C-numbers) formed from FTP before the refining to a particular fuel or chemical distribution.

Note that CO<sub>2</sub> and H<sub>2</sub>O are waste effluents from the process, of which 1-mole each of CO<sub>2</sub> and H<sub>2</sub>O are formed in the gasification process. Also, pure oxygen must be added. The carbon efficiency of gasification is about 7 moles/8 moles=87.5% which is also the result for the overall process if all the CO is converted to liquid fuel. Actual conversion rates are about 50-90% depending on the process.

The energy for conversion is provided by the partial oxidation of the CH<sub>4</sub> and the fact that the FTP is exothermic. The energy efficiency of CH<sub>4</sub> is reduced from its maximum by the generation of half of the H<sub>4</sub> converted to H<sub>2</sub>O in the gasification process. There is an added decrease due to the CO<sub>2</sub> formed. Methane not reacted is separated and returned to the partial oxidation process, or along with methane effluent from the FTP is routed to power generation equipment.

The GTL tradition has dictated that in the other XTL applications, enough hydrogen is provided to generate most of the waste effluent as water, as in the GTL. Hydrocarbon fuels have a molar ratio of H<sub>2</sub>/C~1.1, whereas CH<sub>4</sub> is 2.0 and tradition tries for H<sub>2</sub>/CO=2.15 in the syngas as above in order to yield the extra H<sub>2</sub> needed for the 7 additional moles of water effluent.


#### WTL Example with Electric Heating for Gasification

The GTL tradition of H<sub>2</sub>/CO~2 is impractical and unnecessary when using electrical gasification methods. Application of electrical pyrolysis to CH<sub>4</sub> is inappropriate, but can easily be applied to MSW and biomass waste streams. A typical formula for MSW based on the EPA fact sheet of discards (non-recyclables) of 2012 and modified to the proposed project is C<sub>6</sub>H<sub>10</sub>O<sub>3</sub>. This has been written in a form comparable to cellulose (C<sub>6</sub>H<sub>10</sub>O<sub>5</sub>). Biomass is given as CH<sub>1.5</sub>O<sub>0.7</sub>, or C<sub>6</sub>H<sub>9</sub>O<sub>4.2</sub> as with cellulose (Ibid., p. 39).

## 12

Considering the organics of MSW, its C/O molar ratio is 6/3=2 needing more O<sub>2</sub>; its H<sub>2</sub>/CO ratio is 5/6=0.83 needing more H<sub>2</sub>. Gasification to a viable syngas of CO & H<sub>2</sub> then needs additional moisture (most of which is within the MSW if not dried) and oxygen. The SAF gasifier can then recycle FTP effluents H<sub>2</sub>O and CO<sub>2</sub> (to provide not only oxygen but additional CO to increase yield). Pure oxygen could be added, but is not needed with the electrically generated pyrolysis and gasification and with the H<sub>2</sub>O and CO<sub>2</sub> available from the FT process, thus saving the cost of pure oxygen.

A selected reaction might be:



The syngas is essentially all CO and H<sub>2</sub> because the process is at sufficient temperatures to give negligible CO<sub>2</sub> and H<sub>2</sub>O (as well as any other hydrocarbons) per equilibrium reaction calculations

The theoretical performance parameters indicate a C-efficiency of 7/7=100% for gasification (including the added CO<sub>2</sub> as input) and 4.67/7=66% for the FT conversion or 66% overall. Since the internally recycled CO<sub>2</sub> is not an external feedstock, the carbon efficiency of gasifying the feedstock is 7/6=117%, and for the liquid fuel production is 4.67/6=78%.

If H<sub>2</sub>/CO=7/7=1 for gasification, then it is much below the traditional value of ~2.15. This is possible because of the electrical heating instead of partial combustion. Actual overall conversion rates are about 50-90% depending on the FT process.

The other difference from traditional processes is that the "excess" oxygen from CO in FT synthesis must also be carried away by the CO<sub>2</sub> as well as the H<sub>2</sub>O. This decreases the yield of liquid fuels per mass of MSW, but is more than made up for with the additive CO<sub>2</sub>. The SAF processing does not result in as much waste water effluent, and part of this is needed for recycling through the SAF. The result is a reduction in the carbon footprint and the amount of final waste water from the FT process. In this ideal case, 1 mole per 2.3 of CO<sub>2</sub> generated (43.5%) is recycled.

#### Operation

Prior Patent of which this is an Extension

As shown in FIGS. 1 & 2, unsorted MSW 1-A (with the exception of extremely bulky items that are manually sized) is dumped into a pit, loaded into a hopper 2, and routed to a crusher-compactor-feeder system 7 to be fed into the middle of the electric furnace, shown as a SAF 8. The thus-sized MSW 1-B forms a cold top 11 above a previously formed molten slag 10. The power supplied through the electrodes 12 passing through the SAF 8 roof generates a concentrated electromagnetic field in the molten slag. The magnetic field rotates the ~1700 C electrically-conducting, molten slag 10 so as to distribute the MSW into the cold top 11 covering the slag. The surface of the cold top has been measured at a temperature of ~1300 C. The test facility with which experimental evidence has been determined is shown in FIG. 4.

Metal in the MSW 1 is melted into a 1650 C molten metal layer 9 at the bottom of the SAF 8 until it builds up sufficiently to be tapped 3 into metal ingots. Inorganic materials such as ash, dirt, bricks, and glass in the MSW 1 are melted to sustain the slag layer 10, which is tapped 4 at 1650-1700 C to be cast into construction products. FIG. 4

## 13

shows the patented (U.S. Pat. No. 6,299,830) remote-controlled tapping device in operation.

The organic material in the cold top **11** settles in to over 1300 C to become pyrolyzed and mostly gasified prior to leaving the SAF **8**. The steam additive **5** and the CO<sub>2</sub> additive **6** are injected into the SAF **8** to react chemically with the cold top **11** and its offgas. The injection is also used to create turbulence in the top of the SAF **8** to enhance reduction reactions. The offgas **13** leaves the SAF **8** through a constrictor **14** to the gasifier **15** at approximately 1100 C as controlled by the power to the electrodes **12**.

The constrictor **14** serves to decrease particulate carryover to the gasifier **15**. The gasifier **15** provides additional residence time for the gasification to take place. It is well insulated and a temperature drop of only 50-100 C has been calculated. Additional heaters can be placed in the gasifier **15** to increase temperatures if needed.

FIG. **3** shows an isometric drawing of a proposed 500 tonne/day MSW electric furnace plant in the SAF configuration. The range of the two electrodes is shown as rotated via electrode drive U.S. Pat. No. 5,914,979.

#### Equilibrium-based WTL Example

The reactions discussed in the Description are "ideal" in that they assume completion to the desired components. The following is the adjustment based on pyrochemical calculations assuming sufficient time to obtain equilibrium compositions at pressure and temperatures involved. Design calculations have shown this to be highly probable. Also included in the analysis are the FT Products calculations to be discussed later.

For the MSW product considered here as an example, test data from a FTP process is used to demonstrate the energy recovery methods. The example is for 500 tpd of MSW as prescribed above (66.5% organics, 15% moisture, 18.5% other) with additives of 5% moisture and 19% CO<sub>2</sub> (where the last additives are a percent of and added to the 500 tpd of MSW giving 620 tpd total) and are in the range of an optimum case. The input organic mass flow rate is then 332.5 tpd MSW-organics, 75 tpd MSW-moisture, 25 tpd added moisture, and 95 tpd added CO<sub>2</sub>. The FTP effluent output is predicted at approximately 125 tpd water and 284 tpd CO<sub>2</sub>, of which 25 tpd water and 95 tpd are additives and the remainder excess waste effluents.

The additive amounts were obtained after many perturbations utilizing pyrochemical equilibrium calculations, potential additives CO<sub>2</sub>, CH<sub>4</sub>, H<sub>2</sub>O and O<sub>2</sub>, prorating liquid fuel generation with test values, and integrating the FTP effluents as additives to the SAF.

The following optimum reaction relations were developed. On a mass basis the input to the syngas generator for the particular site considered above is:

66.5% MSW-Organics+15% MSW-Moisture+5%  
Added H<sub>2</sub>O+19% Added CO<sub>2</sub>

On a molar basis:

C<sub>6</sub>H<sub>10</sub>O<sub>3</sub>+1.629H<sub>2</sub>O<sub>msw</sub>+0.543H<sub>2</sub>O<sub>add</sub>+  
0.844CO<sub>2</sub>→ input composition

→5.95CO+5.83H<sub>2</sub>+0.034CH<sub>4</sub>+0.015CO<sub>2</sub>+  
0.003H<sub>2</sub>O→ syngas composition

→(—CH<sub>2</sub>—)+2.015CO<sub>2</sub>+2.003H<sub>2</sub>O+0.034CH<sub>4</sub>, FT conversion

where the syngas composition is based on the 1 mole of C<sub>6</sub>H<sub>10</sub>O<sub>3</sub> put in.

Note that the carbon conversion efficiency for this electrical gasification is 5.95/6=99.2% if the recycled CO<sub>2</sub> is

## 14

excluded. In the FTP relation, the reason 6 (—CH<sub>2</sub>—) are not obtained is that free oxygen would be formed which then oxidizes the (—CH<sub>2</sub>—) or equivalent to CO<sub>2</sub> (and/or CO) and H<sub>2</sub>O. The FTP carbon efficiency is now 4/6=67% if all CH<sub>2</sub> radicals are converted to liquid fuel, compared to 78% for the ideal WTL or 83% for the ideal GTL process.

One can add more hydrogen, but with H<sub>2</sub>O it would be a breakeven proposition since the end product would be H<sub>2</sub>O and the added input H<sub>2</sub>O needs to be dissociated or the equivalent. If add CH<sub>4</sub>, the process is closer to the GTL, but results in just turning the CH<sub>4</sub> added into liquid fuel as in a GTL or end up with more CH<sub>4</sub> in the Syngas, so why bother in a SAF for solid wastes. If add more CO<sub>2</sub>, obtain more O<sub>2</sub> than can use and then get more CO<sub>2</sub>, thus self-defeating. CO<sub>2</sub> only helps when the feedstock is oxygen limited.

The conclusion is that when processing MSW and the similar biomass or even coal, the waste effluents will be both H<sub>2</sub>O and CO<sub>2</sub>. The present embodiment shows how to do this most effectively.

The estimated equilibrium syngas compositions are calculated with pyro-metallurgical software, METSIM by Proware at the temperatures estimated in the SAF **8** above the melt at 1300 C and the gasifier **15** at a conservative 1000 C. The syngas **16-A** is assumed to leave the gasifier **15** and enter a heat exchanger **17** at a minimum of 900 C. Heat transfer losses calculated for the well-insulated gasifier **15** indicate the temperature should be at least 50 C higher. The significant compositions found using METSIM under Gibbs equilibrium conditions are given in Table 1. Limiting conditions for some of the perturbations calculated are also shown in Table 1.

The FTP system for this 500 tpd SAF plant example is a Fe-LTFT (iron catalyst, low-temperature, 230-240 C, FT synthesis system). The FTP effluents, H<sub>2</sub>O (as saturated liquid) and gaseous CO<sub>2</sub> are assumed to be available at ~200 C and 15 atm pressure. For other FTP systems, design adjustments can be made. In application, the FTP will be dependent on the commercial provider.

Extensions of Rentech data from DOE 2000 report (Natural Gas to Liquids Conversion Project, Raytheon Engineers & Contractors, DOE Report 2000-1032585, 2000) from GTL/CH<sub>4</sub> processing to that of the MSW provided a basis for determining the difference in the syngas composition. Estimates of the conversion of the HCLF generated are based on carbon content and then prorated based on the amount of hydrogen available. The oxygen from CO unable to be combined with hydrogen would be combined with CO to make CO<sub>2</sub>. If no additives are input with the feedstock, the yield of HCLF is greatly reduced. Adding CO<sub>2</sub> and H<sub>2</sub>O to make up for hydrogen and oxygen deficiencies in the feedstock, and iterating over perturbations of the additives to eliminate free oxygen and H<sub>2</sub> results in an optimum amount of additives, as well as an estimate of the CO<sub>2</sub> and H<sub>2</sub>O waste from the FTP.

A FT Products spreadsheet calculation is used to optimize the additive wt % as well as what additives to use. CO<sub>2</sub>, H<sub>2</sub>O, CH<sub>4</sub>, and pure O<sub>2</sub> were examined as potential additives. The optimum is found, based mainly on the yield of liquid fuel products, the availability of the additives, and the relative costs per gallon of that fuel for different additive combinations (see Tables 2A & 2B). The optimum result was found to be 5 wt % H<sub>2</sub>O and 19 wt % CO<sub>2</sub> additives.

TABLE 1

Selected syngas equilibrium compositions for syngas leaving Gasifier via METSIM.									
T <sub>equilibrium</sub> is taken at 1000 C in Gasifier.									
Units are in wt % of MSW input unless designated. MSW organics incl. 0.8% sulfur totals 82.3 wt % of MSW.									
Small concentrations are given more significant digits.									
Run Label	A	B	C	G4	G1 = G3	G6	Q	D	F2
Run ID	As Is No Add	Min H2O	Add CO2	5/18/0/0	5/19/0/0 Optimum	7/18/0/0	8/15/5/0	Pure O2	4/12/0/3
Des- cription	No Additives	Add 8% H2O	Add 20% CO2	Add 5 wt % H2O; 18 wt % CO2	Add 5 wt % H2O; 19 wt % CO2	Add 7 wt % H2O; 18 WT % CO2	Add 8 wt % H2O; 15 wt % CO2, 5 wt % CH4	Add 7 wt % O2	Add 4 wt % H2O; 12 wt % CO2; 3 wt % O2
CH4	11.467	4.398	4.220	0.531	0.324	0.083	3.945	4.493	0.574
CO	66.231	78.620	91.640	96.474	97.370	96.390	97.680	78.450	92.600
CO2	0.000	0.021	0.022	0.250	0.416	1.619	0.036	0.017	0.218
H2	3.908	6.568	5.720	7.204	7.244	7.435	7.938	5.652	7.083
H2O	0.000	0.152	0.012	0.164	0.273	1.100	0.025	0.011	0.147
O2	0	0	0	0	0	0	0	0	0
C1	0	0	0	0	0	0	0	0	0
CS	0.000821	0	0.000182	0.0000147	0.00000893	0.000002	0	0.000173	0.0000158
CS2	0.164	0	0.0294	0.00194	0.00118	0.00028	0	0.02836	0.00212
COS	0.0618	0.0536	0.0687	0.0596	0.0599	0.0579	0.05507	0.05997	0.0582
SO2	0	0	0	0	0	0	0	0	0
S2	0.000198	0	0	0.000123	0.000122	0.000118	0.000117	0	0
H2S		0.8199	0.7848	0.8146	0.8151	0.817	0.8189	0.791	
wt % Sum	81.8	90.6	102.5	105.5	106.5	107.5	110.5	89.5	100.7
COS			1.0804446	0.0135	0.014	0.0134	0.01191		0.0141
(vol %) H2S				0.33	0.336	0.333	0.3122		0.347
(vol %) H2/CO	0.826	1.169	0.874	1.045	1.042	1.08	1.138	1.019	1.071
molar C/O	1.303779	1.0945572		1.006957	1.0014604	0.98421484	1.07020874	1.100071786	1.001
molar									

TABLE 2A

Liquid fuel product results for different Additives for 500 tpd MSW plant: Input and fuels produced.									
Run Label	A	B	C	G4	G1 = G3	G6	Q	D	F2
Run ID	As Is No Add	Min H2O	Add CO2	5/18/0/0	5/19/0/0 Design Case	7/18/0/0	8/15/5/0	Pure O2	4/12/0/3
Description	No Add	Add 8% H2O	Add 20% CO2	Add 5 wt % H2O; 18 wt % CO2	Add 5 wt % H2O; 19 wt % CO2	Add 7 wt % H2O; 18 WT % CO2	Add 8 wt % H2O; 15 wt % CO2, 5 wt % CH4	Add 7 wt % O2	Add 4 wt % H2O; 12 wt % CO2; 3 wt % O2
Input									
500 tpd MSW-avg_2012	501	501	501.0	501	501	501	501	501	501
Moisture in IWS	75	75	75.0	75	75	75	75	75	75
Added(+), dried (-) or excess water	0	40	0.0	25	25	35	40	0	20
CO2 Recycled from FTP	0	0	100.0	90	95	90	75	0	60
Added CH4 to get more H2	0	0	0.0	0	0	0	25	0	0
Added O2 for excess C and to provide energy	0	0	0.0	0	0	0	0	35	15
Non organics (ash, metal, Cl/S, N2)	92.5	92.5	92.5	92.5	92.5	92.5	92.5	92.5	92.5
Organics in IWS	333.5	333.5	333.5	333.5	333.5	333.5	333.5	333.5	333.5
Net organics to Syngas (excl. N2)	333.5	333.5	433.5	423.5	428.5	423.5	433.5	333.5	393.5
Net Water to syngas	75	115	75.0	100	100	110	115	75	95
Syngas H2 & CO	408.5	448.5	508.5	523.5	528.5	533.5	548.5	408.5	488.5
H2/CO molar syngas to FTP	0.83	1.17	0.87	1.05	1.04	1.08	1.14	1.01	1.07
C/O molar Syngas to FTP	1.0000	0.9993	0.9996	0.9957	0.9930	0.9726	0.9994	0.9996	0.9961
Liquid Fuels Produced									
Naphtha Produced (BPD)	17.1	20.4	23.8	25.0	25.2	25.0	25.3	18.7	23.3
Linear Alpha Olefins (BPD)	18.5	22.0	25.6	26.9	27.2	26.9	27.3	20.2	25.1
Linear Paraffins (BPD)	13.4	15.9	18.5	19.5	19.7	19.5	19.7	14.6	18.2

TABLE 2A-continued

Liquid fuel product results for different Additives for 500 tpd MSW plant: Input and fuels produced.									
Run Label	A	B	C	G4	G1 = G3	G6	Q	D	F2
Diesel Product (BPD)	20.8	24.8	28.9	30.4	30.7	30.4	30.8	22.8	28.3
Kerosene Product (BPD)	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
Wax (C20-C50) (BPD)	52.7	62.6	73.0	76.8	77.5	76.8	77.8	57.5	71.5
Total Liq. Diesel Product	122.4	145.6	169.7	178.7	180.3	178.5	180.9	133.8	166.4
excl Alcohols: TLDF									
Net TLDF accounting	92.9	135.5	132.9	155.2	156.3	158.1	165.5	113.8	146.7
for excess O2									
Mixed Alcohol	6.6	7.9	9.2	9.6	9.7	9.6	9.8	7.2	9.0
Product (BPD)									
Sum of Products	129.1	153.5	178.9	188.3	190.0	188.1	190.7	141.1	175.4

TABLE 2B

Liquid fuel product results for different Additives for 500 tpd MSW Plant: Summaries						
Run Label	A	B	C	G4	G1 = G3	
Run ID	As Is No Add	Min H2O	Add CO2	5/18/0/0	Optimum	
Additives in wt % of MSW (H2O, CO2, CH4, O2)	0, 0, 0, 0	8, 0, 0, 0	0, 20, 0, 0	5, 18, 0, 0	5, 19, 0, 0	
Description	No Add	Add 8% H2O	Add 20% CO2	Add 5 wt % H2O; 18 wt % CO2	Add 5 wt % H2O; 19 wt % CO2	
Summary						
Total Organic Input (tonnes/day)	408.5	448.5	508.5	523.5	528.5	
Liquid HC Output (50/50 Diesel/Naphtha)	69.8	83.0	96.7	101.8	102.8	
Water or Steam Product Output	60.1	115.0	90.4	122.6	123.6	
Wax Product Output	52.7	62.6	73.0	76.8	77.5	
Mixed Alcohol Product Output	6.6	7.9	9.2	9.6	9.7	
CO2 Output	246.6	187.2	324.7	277.9	282.7	
Net CO2 Output	246.6	187.2	224.7	187.9	187.7	
Other Tail Gases: H2 (& CO from H stealing O to H2O)	58.1	22.0	21.1	2.7	1.6	
Other Unknown (to balance excess O2 backoff)	-85.4	-29.2	-106.7	-67.9	-69.5	
METSIM H_Required (kCal/hr) for 100 kg/hr of MSW	146832	179761	168736	197208	198483	
H_Required (MW) for 500 tpd	35.6	43.5	40.9	47.7	48.1	
TLF for 500 tpd (TPD)	129.1	153.5	178.9	188.3	190.0	
TLF Gal/yr at SG =1 (gal/yr)	11,776,528	14,005,057	16,324,044	17,183,140	17,342,033	
Oxygen cost/gal at \$400/tonne						
Electricity cost/gal for H_Req. for TLDF	\$1.84	\$1.54	\$1.48	\$1.48	\$1.48	
at SG =1 & \$0.05/kWh (\$/gal) + the Oxygen Cost						
CH4 in Syngas ((TPD)	11.47	4.40	4.22	0.53	0.32	
Rank (1 is highest rank) and Comment	Starter	Tester	OK	Hi TLDF	Hi TLDF	
High Yield		Not bad	10	2	2	
High CO2 recycle			1	3	2	
Low cost/gal (best about the same)			2	2	2	
Simplicity			1	2	2	
CH4 in Syngas			3	2	2	
Diesel C-Conversion Efficiency = C-TLDF/C-MSW	41%	60%	59%	69%	69%	
Total C-Conversion Efficiency = C-TLF/C-MSW	57%	68%	80%	84%	84%	
Liquid fuel product results for different Additives for 500 tpd MSW Plant: Summaries						
Run Label	G6	Q	D	F2		
Run ID	7/18/0/0	8/15/5/0	Pure O2	Some O2		
Additives in wt % of MSW (H2O, CO2, CH4, O2)	7, 18, 0, 0	8, 15, 5, 0	0, 0, 0, 7	4, 12, 0, 3		
Description	Add 7 wt % H2O;	Add 8 wt % H2O; 15 wt % CO2,	Add 7 wt % O2	Add 4 wt % H2O; 12 wt % CO2; 3 wt % O2		
	18 WT % co2	5 wt % CH4				
Summary						
Total Organic Input (tonnes/day)	533.5	548.5	408.5	488.5		
Liquid HC Output (50/50 Diesel/Naphtha)	101.7	103.1	76.3	94.8		
Water or Steam Product Output	132.5	137.9	87.0	117.8		
Wax Product Output	76.8	77.8	57.5	71.5		
Mixed Alcohol Product Output	9.6	9.8	7.2	9.0		
CO2 Output	271.4	244.8	217.7	249.7		
Net CO2 Output	181.4	169.8	217.7	189.7		
Other Tail Gases: H2 (& CO from H stealing O to H2O)	0.4	19.7	20.7	2.8		
Other Unknown (to balance excess O2 backoff)	-58.9	-44.6	-58.0	-57.1		
METSIM H_Required (kCal/hr) for 100 kg/hr of MSW	200251	209562	146075	182930		
H_Required (MW) for 500 tpd	48.5	50.7	35.4	44.3		

TABLE 2B-continued

TLF for 500 tpd (TPD)	188.1	190.7	141.1	175.4
TLF Gal/yr at SG =1 (gal/yr)	17,167,282	17,397,251	12,871,869	16,002,438
Oxygen cost/gal at \$400/tonne			\$0.49	\$0.16
Electricity cost/gal for H <sub>2</sub> Req. for TLDF	\$1.47	\$1.47	\$1.98	\$1.61
at SG =1 & \$0.05/kWh (\$/gal) + the Oxygen Cost				
CH <sub>4</sub> in Syngas ((TPD)	0.08	3.95	4.49	0.57
Rank (1 is highest rank) and Comment	Hi TLDF	Hi TLDF	Poor	Hi cost
High Yield	2	1	10	3
High CO <sub>2</sub> recycle	3	4	10	5
Low cost/gal (best about the same)	1	1	9	3
Simplicity	2	3	1	3
CH <sub>4</sub> in Syngas	1	3	3	2
Diesel C-Conversion Efficiency = C-TLDF/C-MSW	70%	74%	51%	65%
Total C-Conversion Efficiency = C-TLF/C-MSW	84%	85%	63%	78%

15

If CH<sub>4</sub> is available from the tail gas recycling, the impact is insignificant. The cost of pure oxygen addition is similar to other costs, but then less CO<sub>2</sub> (as the oxygen source) can be recycled and total yield is reduced. Of significance is that a variation of the additive wt % for the optimum case of 20% does not change the yield significantly. This suggests a very robust compositional variation for the present embodiment.

Detailed calculations of heat exchanger geometries and pipe sizes required, fluid heat transfer coefficients, and overall heat transfer coefficients between the syngas and the coolants to determine the temperatures available (or required

forth. The Descriptions indicate the use of the coolant being heated. HP is high pressure, MP is medium pressure, LP is low pressure, GT is gas turbine, and ST is steam turbine.

The order and temperatures for the heat exchangers (HX) so numbered and described are given in Table 3. The component numbers as shown in FIG. 2 are given in front of the HX designation in Tables 3, 4 and 5. NA denotes those not explicitly shown in FIG. 2. The conditions selected are to obtain maximum temperatures of the recycled additives to the SAF and the most electrical power to reduce the net power needed.

TABLE 3

Order, description and temperatures over heat exchangers for the example. The leaving syngas temperature is the next syngas inlet temperature.				
Heat Exchanger	Description	T <sub>syngas_in</sub> (C)	T <sub>CO<sub>2</sub>_in</sub> (C)	T <sub>CO<sub>2</sub>_out</sub> (C)
17 HX1	CO <sub>2</sub> 1 <sup>st</sup> Cycle to SAF at LP	900.0	528.3	799.0
19 HX2	CO <sub>2</sub> 1 <sup>st</sup> Cycle Reheat at MP to GT1	872.7	535.5	700.0
21 HX3	CO <sub>2</sub> 1 <sup>st</sup> Cycle Heat at HP to GT2	856.7	200.0	700.0
NA HX4	CO <sub>2</sub> 2 <sup>nd</sup> Cycle Reheat at MP to GT3	808.9	535.5	700.0
NA HX5	CO <sub>2</sub> 2 <sup>nd</sup> Cycle Heat at HP to GT4	792.3	200.0	700.0
NA HX6	CO <sub>2</sub> 3 <sup>rd</sup> Cycle Reheat at MP to GT5	744.5	563.4	700.0
NA HX7	CO <sub>2</sub> 3 <sup>rd</sup> Cycle Heat at HP to GT6	730.5	200.0	700.0
22 HX8	H <sub>2</sub> O to SAF (Bled off ST2)	682.2	244.7	590.0
26 HX9	H <sub>2</sub> O to ST1 and ST2	665.7	200.0	600.0
27 HX10	H <sub>2</sub> O to ST3 (separate Rankine cycle)	566.0	150.0	500.0

to/from turbines) were made. Banks of heat exchangers for each syngas-coolant were set up in columns of variable diameter pipe rows determined as above. The banks were sequenced by trial and error to give the optimum arrangement to satisfy the desired criteria: maximum temperatures of additives into the SAF, maximum turbine power for the pressures dictated by the FTP used, and an appropriate temperature differential between the syngas and the coolant in the heat exchangers, as well as the need to have the most rapid cooling most upstream for quenching the syngas to prevent the reformation of complex hydrocarbons. These spreadsheet calculations were then verified via an ASPEN software calculation (M. McKellar, et al., Aspen Process Model for the Misty Mountain Resource Recovery Plant, INL TAP Report INL/LTD-15-36850, October 2015).

#### Results for Example Case

A more complex arrangement than FIG. 2 occurs for the 500 tpd MSW plant for which three (3) FTP waste CO<sub>2</sub> flows of 95 tpd each, were determined. One CO<sub>2</sub> flow 45 feeds the SAF along with a water/steam 51 reuse as is shown in FIG. 2 and listed in Table 3. The varied pattern of the coolants of the syngas is apparent in the list of temperatures. HX1 17 is the first heat exchanger the Syngas sees, and so

Table 3 lists three CO<sub>2</sub> Gas cycles, but FIG. 2 shows only one. That is because there is 3 times as much CO<sub>2</sub> available from the FTP as needed for the additive. Therefore, three CO<sub>2</sub> Brayton gas cycles each with one reheat stage were set up identically, except for the 1<sup>st</sup> cycle, after which gas turbine GT1 18 the CO<sub>2</sub> is reheated in GT1 17 and routed 6 to the SAF 8. As a result, each gas cycle has entering CO<sub>2</sub> from the FTP 45 at 200 C and 15 atm, as well as any excess CO<sub>2</sub> 36 not used by the feeder assembly 7 (not shown). The syngas 16 heats the CO<sub>2</sub> 45 up to 700 C in HX3 21 to enter the high pressure turbine 20. The steam 51 is not heated to as high a temperature and therefore is located at the end of the syngas heat exchanger chain.

An alternative for HX1 17 is to use a water-wall unit first to cool the syngas. It is also possible to rearrange the order of the coolant heat exchangers to get higher temperature syngas to transfer heat to higher temperature coolants, but the simpler configuration in FIG. 2 is easier to understand.

Table 4 indicates the mass flow rates, pressures, temperatures and electrical power output for the CO<sub>2</sub> powered turbines. The six CO<sub>2</sub> turbine systems of the three CO<sub>2</sub> flows of 95 tpd are set up to operate identically except for the

21

exhaust of GT1 18, which CO<sub>2</sub> 6 has been heated in HX1 17 to be added to the SAF 8. The exhaust from GT3 ~18 and GT5 ~18 are at 528.3 C which can be used to heat additional rankine cycles, help boil the FT liquid water or other waste heat activities. The pressure is too low (~1 atm) to use in a turbine directly.

TABLE 4

Selected thermal properties of the CO <sub>2</sub> turbine processes and power developed.						
Turbine System	Mass Flow (tpd)	p <sub>in</sub> (kPa)	p <sub>out</sub> (kPa)	T <sub>in</sub> (C)	T <sub>out</sub> (C)	Power (MWt)
18 GT1	95	397.2	101.3	700	528.3	0.2235
20 GT2	95	1489	405.3	700	535.5	0.2143
~18 GT3	95	101.3	397.2	700	528.3	0.2235
~20 GT4	95	1489	405.3	700	535.5	0.2143
~18 GT5	95	397.2	101.3	700	528.3	0.2235
~20 GT6	95	1489	405.3	700	563.4	0.1786
Total MWe from CO <sub>2</sub>						1.2777

Table 5 indicates the mass flow rates, pressures, temperatures and electrical power output for the H<sub>2</sub>O powered turbines 23 & 28. Only 25 tpd is needed for the additive H<sub>2</sub>O 5 of the 125 tpd available. It is obtained by reheating part of the steam run through ST2 23 to 590 C before injecting the steam 5 into the SAF 8. Each of the turbines has a different flow rate because the steam heating is balanced to the syngas energy available.

TABLE 5

Selected thermal properties of the steam turbine processes and the power developed.						
Turbine System	Mass Flow (tpd)	p <sub>in</sub> (kPa)	p <sub>out</sub> (kPa)	T <sub>in</sub> (C)	T <sub>out</sub> (C)	Power (MWt)
23 ST1	100	101.3	34.47	244.7	156.7	0.1968
23 ST2	125	1489	101.3	600	244.7	1.057
28 ST3	134.5	1460	34.47	500	93.09	1.247
Total MWe from H <sub>2</sub> O						2.498

There is more than double the power generated by the steam-Rankine cycles at much lower temperatures than by the CO<sub>2</sub>-Gas/Brayton cycles. The difference is caused by a combination of the greater change in temperature and higher mass flow rates in the steam cycles.

Following the last heat exchanger 27, conventional air pollution control equipment is used as the syngas primary clean-up system. The syngas 16-B is cooled to approximately 200 C prior to the filter baghouse 33. Syngas particulate 53 is collected from the filter baghouse 32 with the particulate (mostly silica) returned to the SAF feeder 7. The syngas acid gas is then scrubbed out by a scrubber 33. The syngas 16-B is further cooled in the scrubber to approximately 50 C. This energy is used to help boil the compressed water for HX10 27. A separate cooler 54 is used to maintain scrubber temperatures. The scrubber blowdown 55 is evaporated to retrieve acid salts. The syngas 16-C is then compressed to 15 atm for this example by a compressor 56 and stored temporarily in tanks 57 for input to the FTP 52.

A simple FT synthesis and refinery plant 52 outlined in FIG. 2 is included to show the sources of the additives CO<sub>2</sub> 6 and H<sub>2</sub>O 5. The compressed syngas 16-D flows into a Rectisol™ or equivalent S-cleanup system 34 that separates it into three streams. The top stream contains H<sub>2</sub>S and CO<sub>2</sub>

22

which are processed in a Sulfolin™ or equivalent S-recovery process 35 to separate any sulfur 37 and CO<sub>2</sub> 36. CO<sub>2</sub> 36 provides a blanket gas to the feeder 7 in order to reduce the air and nitrogen in the void spaces. Any excess CO<sub>2</sub> from the blanket gas is blended with CO<sub>2</sub> 51 from the FT refinery 48.

The middle stream from S-cleanup 34 contains the liquid naphtha that goes to a naphtha liquid refinery 38 to generate chemicals 39 and fuels 40.

The third stream of clean syngas enters the FT catalytic synthesis process 41. The syngas is further separated into gases 42, oil product and waxes 46, and aqueous product including alcohols 47. The latter two are processed in a FT refinery 48 to make chemicals 49 and fuels 50 and to generate the waste water 51 that is recycled through HX9 26 to the steam turbine ST2/1 23 cycle with the take off to SAF 8 as steam additive 5. The gas products 42 from the FTS process go to a Benfield CO<sub>2</sub> separation unit 43 where CO<sub>2</sub> 45 is separated from tail gas 44 of any remaining CO, H<sub>2</sub>, CH<sub>4</sub>, N<sub>2</sub>, etc. The CO<sub>2</sub> 45 is routed to the HX3 21, and its sisters HX5 and HX7 ~21. The tail gas 44 can be recycled back into the FTS 41, as often done to improve conversion efficiency, or it can be recycled into the SAF 8 with the CO<sub>2</sub> 6. In the latter case, there is no reason to include the Benfield process. The recycling of the tail gas 44 to the FTS 41 will depend on the commercial FTS process selected. If the tail gas quantity is small and its composition is not principally CO and H<sub>2</sub>, then it can be recycled back into the SAF 8. Excessive nitrogen can be culled out. If CH<sub>4</sub> concentrations are high in the tailgas, it can be used to generate more electric power.

Table 6 is a summary of the heat use and recovery by various components. The energy to melt the metal and slag is a small fraction of the energy to gasify. That is why the economics of metal recovery and casting of the molten slag from the inorganics is more favorable than making electricity or liquid fuels from the organics. The energy added by the additives is misleading because it is their mass enthalpy added to the syngas that counts in addition to that which came from the syngas and that from the FTP. The HX heating is meaningful in that there is a double savings because one does not then have to heat the Additives by that much to get the desired syngas composition.

The results show that the CO<sub>2</sub> additive can be heated to ~800 C and the H<sub>2</sub>O additive heated to ~590 C, while recycling the energy available from FT synthesis and syngas cooling. In addition, approximately 5 MWe power are generated to reduce the external electricity needed by the SAF.

TABLE 6

Summary of the heat required and recovered by various components (component heat losses are included).	
Component	MW
SAF - metal & slag melting	0.71
SAF pyrolyzation/gasification	42.10
SAF-gasifier heating of additive CO <sub>2</sub> & H <sub>2</sub> O	4.90
Total provided through SAF power	47.71
CO <sub>2</sub> turbine power cogeneration	-1.28
H <sub>2</sub> O turbine power cogeneration	-2.50
Net electrical energy required by SAF	43.93
Energy recovered by reheating additives	
CO <sub>2</sub> in HX1 (included above)	0.36
H <sub>2</sub> O in HX8 (included above)	0.21
Waste heat from FTS, CO <sub>2</sub> exhaust or other to heat water to 150 C. for separate Rankine Cycle	0.56

In addition to energy savings, the embodiment reduces the carbon footprint by recycling the CO<sub>2</sub> into the SAF. Miglio, Zennaro and de Klerk (Ibid., Environmental Sustainability chapter, p 329) present the CO<sub>2</sub> footprint due to the raw material feed. Several of their raw materials relevant to this work are shown in Table 7. The effective H:C ratios are not well explained but apparently are caused by the hydrogen being used for the hydrogenation of heteroatoms, thus reducing the hydrogen that is effective.

TABLE 7

Comparison of the CO <sub>2</sub> footprint from various materials and sources.				
Feed Material	H:C Ratio		CO <sub>2</sub> footprint	
	Nom- inal	Effec- tive	due to Feed (kg CO <sub>2</sub> /KG HC)	Source
Natural gas (CH <sub>4</sub> )	4.00	4.00	0.00	Miglio, et al.
MSW refuse	1.83	0.65	3.96	"
Biomass-switchgrass	1.45	0.12	5.75	"
Coal-III#6 bituminous	0.77	0.43	4.60	"
MSW-EPA 2012	1.67	0.59	4.34 - 1.45 = 2.89 net	This work

Table 7 indicates that the carbon footprint of a typical Waste-to-energy plant processing of MSW is approximately 3.96 kg-CO<sub>2</sub>/kg-HC. Prorating this work to their MSW reference work gives an effective H:C of 0.59 and a footprint of 4.34. Their discussion indicates that the FTP does not affect the CO<sub>2</sub> footprint significantly compared to the overall footprint. For the present example, the recycled CO<sub>2</sub> is approximately 33% of the total CO<sub>2</sub> generation or 1.45 kg-CO<sub>2</sub>/kg-HC. Subtracting that from the 4.34 gives 2.89 kg-CO<sub>2</sub>/kg-HC. In this calculation, the CO<sub>2</sub> contribution of the electric power plant has not been taken into account, but there is a reduction in the CO<sub>2</sub> footprint of the SAF-FTP systems of 33%.

Economic considerations of the cost of electricity is often used to discard consideration of electric arc processing, prematurely. The convenience of SAF gasification to a relatively pure syngas with high carbon-efficiency, the ability to process heterogeneous MSW compositions easily with a concentrated energy source, the generation of a separate homogeneous molten "slag" from which high-value construction products can be cast, and the recycle ability of FTP waste CO<sub>2</sub> and H<sub>2</sub>O to decrease the carbon footprint and amount of waste water overcome the initial electrical prejudices. These factors contribute to the bottom line, showing the economics favors the novelty of the SAF gasification process as presented here.

#### CONCLUSIONS, RAMIFICATIONS AND SCOPE

The embodiment is the linking of a liquid fuels synthesis process, such as a Fischer-Tropsch synthesis and refinery system, to an electric furnace process, such as a submerged arc furnace to increase liquid hydrocarbon product yield, decrease electrical costs, decrease the carbon footprint of the combined systems, and to be able to process MSW, biomass, and coal effectively (which without additives give H<sub>2</sub>/CO molar ratios of less than unity). The electrical process can be done without having to force the syngas H<sub>2</sub>/CO molar ratio greater than 2, as done with partial oxidation methods.

The advantages of the novelty of the present embodiment is that by linking an electric gasification process with the CO<sub>2</sub> and H<sub>2</sub>O effluent waste products from the FT synthesis process:

- 1) essentially no sorting of the MSW to separate inorganics and metal is required.
- 2) less external electric energy is required,
- 3) the yield of liquid fuels is increased over that from the original organic feedstock because the addition of the waste CO<sub>2</sub> from the FTP increases the CO syngas content,
- 4) the footprint of CO<sub>2</sub> from the FT process is significantly smaller than if CO<sub>2</sub> is not recycled,
- 5) The syngas cooling can be transferred to the FT process waste CO<sub>2</sub> & H<sub>2</sub>O at high pressure to increase the electric power that can be cogenerated to reduce overall electrical consumption.
- 6) the addition of pure oxygen is not required, and
- 7) the amount of steam added is reduced from the traditional formulation.

The Ramifications of the embodiment are to extend electric arc furnace processing of MSW and C&D waste to generate liquid fuels and chemicals, and to help eliminate distribution of said waste to landfills and the associated liabilities.

The scope of the application is world wide, to collected MSW and to mine landfill MSW, to construction and demolition waste, and to biomass waste. The application can be applied to alcohol synthesis systems as well as FTP, and thereby can be used to generate a wide range of fuels and chemicals.

A major caveat to obtain the above conclusions, is that the syngas generation system must be able to accept and utilize the recycled FTP CO<sub>2</sub> and H<sub>2</sub>O effluents in concert with a heterogeneous feedstock in an appropriate manner. The graphite-electrode arc melter operating in the submerged arc furnace (SAF) model has the advantages required to optimize the generation of the syngas, as well as to separate and process the inorganic and metallic materials usually associated with the types of waste materials to be converted, namely, municipal solid waste, construction and demolition waste, medical waste, and biomass.

This embodiment has not been proposed by others previously because one must use the appropriate apparatus, couple the syngas generation and FTP systems in a novel manner, and devise the complex process procedures to optimize the task economically.

We claim:

1. A method of preparing liquid fuels from syngas, comprising:

- a) providing a waste conversion reactor having a decomposition chamber wherein waste materials comprising organic and inorganic waste is pyrolyzed to produce a high temperature syngas from said organic material and slag from decomposition of said inorganic waste; said waste conversion reactor comprising a submerged arc furnace or plasma torch furnace which supplies heat to the decomposition chamber for pyrolysis and decomposition of said organic and inorganic waste materials;
- b) introducing said syngas from step a) to a liquid fuel synthesis system comprising one or more synfuel conversion reactors wherein said syngas is converted into liquid fuel, wherein said synfuel conversion reactors comprises a syngas conversion catalyst; said synfuel conversion reactor operating at a lower temperature than the temperature of syngas exiting the waste conversion reactor, and wherein at least one of said synfuel



25

conversion reactors provides an effluent stream comprising water, carbon dioxide, tail gas or mixtures thereof;

- c) heating at least one of the at least one liquid fuel effluent streams by exchanging heat with high temperature syngas stream exiting from said waste conversion reactor thereby producing a cooled syngas stream and a hot effluent stream;
- d) introducing the cooled syngas stream into the liquid fuel synthesis plant syngas supply inlet and;
- e) introducing at least one hot effluent stream into an inlet of the waste conversion reactor.

2. The method of claim 1, wherein one liquid fuel effluent stream from the liquid fuel synthesis system which exchanges heat with high temperature syngas contains water.

3. The method of claim 1, wherein one liquid fuel effluent stream from the liquid fuel synthesis system which exchanges heat with high temperature syngas contains carbon dioxide.

4. The method of claim 2, further comprising heat exchanging a second liquid fuel effluent stream from the liquid fuel synthesis system comprising carbon dioxide, with high temperature syngas.

5. The method of claim 1, wherein a tail gas effluent stream from the liquid fuel synthesis system is introduced into the waste conversion reactor.

6. The method of claim 1, wherein said hot effluent stream is introduced in turbine to generate power and wherein said

26

effluent stream from said turbine is heat exchange relationship with said high temperature syngas from said waste conversion reactor.

7. The method of claim 1, wherein one or more effluent stream from said synfuel conversion reactor comprising water, carbon dioxide and tail gas is introduced into said waste conversion reactor.

8. The method of claim 6, wherein said power generated from said turbine supplies a portion of the energy required for said submerged arc or plasma arc furnace.

9. The method of claim 1, wherein liquid metal collects in a molten metal zone in the waste conversion reactor below the slag, and the metal is periodically removed.

10. The method of claim 1, wherein the slag is periodically removed from the waste conversion reactor in liquid form.

11. The method of claim 1, wherein the waste materials pyrolyzed in the waste conversion reactor consists essentially of biomass, municipal solid waste, construction, mining waste, and demolition waste, and mixtures thereof.

12. The method of claim 1, wherein said liquid fuel synthesis system comprises least one or more F-T catalytic reactors.

13. The method of claim 1, wherein said liquid fuel synthesis system comprises at least one or more alcohol synthesis reactors.

\* \* \* \* \*




Figure 1. Electric furnace in submerged arc furnace (SAF) configuration.




Figure 2. Typical arrangement of SAF, heat exchangers and turbines to optimize yield with a simplified Fischer-Tropsch synthesis and refinery component system.






Figure 3. Drawing of 500 tonne/day of MSW SAF feed system, electric furnace, gasifier and duct to heat exchangers. Dual electrode movement range shown.


END-ON VIEW OF MTI-200 INSTALLATION




POWER SUPPL., FAN &amp; BAGHOUSE




OFFGAS DUCTS, SCRUB FILTERS, BURNER



FEEDER, MELTER, SP. QUENCH, PACKED BED



MELTER, ELECTRODES, SCRUBBER SYSTEMS



AUTOMATIC TAPPING OF GLASS-CERAMIC



Figure 4. Photographs of an electric furnace SAF facility used for testing.

# EXHIBITS

## Exhibit C

**Listing of Intellectual Property (IP),  
software, documents, physical materials, drawings, books,  
and assets related to plasma, electric arc and a submerged arc furnace  
to be transferred from Seller to Buyer**



B12

## Exhibit C Summary List

The following list provides information primarily related to the MT-200 and HJ-200 Hanjung projects filtered from available personal storage.

- Hard copy or DVDs of digitized scanned drawings including:
  - Available flat drawings of mostly MT200 prototype and HJ-200 projects, including flat prints, master drawings, and some markups, and
  - Hard copy drawing index from file "drawing nos\_50607.xls" dated 6/18/2005,
- A DVD (approximately 904 mb, 6936 files) compiled December 2023 to January 2024 containing electronic drawing, design, and project files, with drawing and project indexes filtered from various backup media sources including:
  - DVDs containing electronic drawing (AutoCad files) backups, (compiled 2001, 2005, 2016)
  - Some 3.5" floppy disc backups
  - Zip drive disc file backups containing drawing, project documentation, and reports
- DVD of digitized Colorado backup tapes or the backup tapes,
- Several boxes of filtered available and relevant engineer working files from the MT-200 and HJ-200 Hanjung projects,
- 3-ring project documentation binders including:
  - Budgets
  - HJ-100 Series Project Management, QA Plan, Work Orders, etc.,
  - HJ-200 11XX series Engineering Design Files
  - HJ-200 Operator Training Manual
  - HJ-200 300r1 Operations Manual
  - HJ-200 4XX series Technical Procedures - Latest Issue List
  - HJ-200 5XX Shakedown Test plans and HJ-200-607 SAT Test Plan
  - HJ-200 6XX SIT and Trial Burn Documents
  - Hanjung Project Letter files
  - Drawing Numbers (Manual) and Work Order forms
  - HJ-200 Structural and Seismic Analysis
  - Air Monitoring Corp Rad monitoring manual
- A photo album containing fabrication, installation and operations photos,
- Several DVDs of digitized testing videotapes,
- DVD image files of 2 old computers, or the computers.

  
 B12